

PRODUCT-DETAILS

OTM125F2C21D230C

OTM125F2C21D230C AUTOMATIC TRANSFER SWITCH



Informations générales

| | |
|------------------------------|---|
| Extension du type de produit | OTM125F2C21D230C |
| Code de produit | 1SCA151418R1001 |
| EAN | 6417019818238 |
| Description courte | OTM125F2C21D230C AUTOMATIC TRANSFER SWITCH |
| Description longue | Automatic transfer switch, motor operated, open transition type 1-0-2. Self-supplied unit with adjustable operating parameters. |

Valeur Circulaire

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC011021D0201 |
| Informations RoHS | 1SCC011020D0201 |

Commande

| | |
|----------------|------------|
| Code douanier | 85365080 |
| Pays d'origine | China (CN) |

Downloads Préférés

| | |
|--|----------------------------|
| Fiche produit, informations techniques | 1SCC308001B0201 |
| Instructions et manuels | 2TFR700025A1001 |
| Mechanical Drawings | OTM63-125_2P_3P_COMPACTATS |

Dimensions

| | |
|----------------------|---------|
| Produit Hauteur Net | 103 mm |
| Produit Longueur Net | 131 mm |
| Poids net | 1.85 kg |

Technique

| | |
|--|----------------------------------|
| Rated Operational Current AC-21A (I_e) | (380 ... 415 V) 125 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 125 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 90 A |
| Rated Operational Current AC-31B (I_e) | (380 ... 415 V) 125 A |
| Rated Operational Current AC-32B (I_e) | (380 ... 415 V) 125 A |
| Rated Operational Current AC-33B (I_e) | (380 ... 415 V) 80 A |
| Rated Operational Power AC-23A (P_e) | (380 ... 415 V) 45 kW |
| Courant thermique conventionnel à l'air libre (I_{th}) | q = 40 °C 125 A |
| Tension assignée de tenue aux chocs (U_{imp}) | 8 kV |
| Tension assignée d'isolement (U_i) | 800 V |
| Tension | 220...240 V AC |
| Courant assigné de courte durée admissible (I_{cw}) | for 1 s 2.5 kiloampere rms |
| Motor Operational Voltage | 220...240 V AC |
| Power Loss | 6.3 W |
| Degré de pollution | 3 |
| Handle Type | Direct mounted handle |
| Fourth Pole Type | Switched - Simultaneous Function |
| Position of Line Terminals | Supplies on Top - Load on Bottom |
| Controller Type | 21D |
| Nombre de pôles | 2 |
| Indice de protection | Front IP20 |
| Transition Type | Open |

Environnement

Statut RoHS

Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificats et Déclarations (Numéro de document)

| | |
|-----------------------------------|-----------------------|
| Déclaration de Conformité - CE | No declaration needed |
| Instructions et manuels | 2TFR700025A1001 |
| REACH Declaration | 1SCC011021D0201 |
| Informations RoHS | 1SCC011020D0201 |

Emballage

| | |
|--------------------------------|---------|
| Emballage Niveau 1 Unités | 1 pièce |
| Emballage Niveau 1 Largeur | 103 mm |
| Emballage Niveau 1 Longueur | 275 mm |
| Emballage Niveau 1 Hauteur | 168 mm |
| Emballage Niveau 1 Poids | 2.05 kg |

Classifications

| | |
|----------------|--|
| ETIM 5 | EC000216 - Switch disconnecter |
| ETIM 6 | EC000216 - sectionneur de charge |
| ETIM 7 | EC000216 - Switch disconnecter |
| ETIM 8 | EC000216 - Switch disconnecter |
| ETIM 9 | EC000216 - Switch disconnecter (low voltage) |
| eClass | V11.1 : 27371403 |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

Catégories

Produits basse tension → Interrupteurs → Inverseurs de sources et by-pass → Compact ATS

