

Declaration of performance

1. Unique identification code of the product-type:

EN 442-2:2014 Annex G

- Figure G.7 : FASSANE PACK

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) is visible on the product packaging label.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Metallic radiators and convectors installed in a permanent manner in construction works, fed with water or steam at temperatures below 120 °C, supplied by a remote heat source.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

Zehnder Group Vaux-Andigny
17, rue des Parachutistes de la France libre
FR-02100 VAUX-ANDIGNY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

None

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product under system 3 covered by a harmonised standard:

CETIAT, 25 Avenue des Arts, BP 52042, FR-69603 VILLEURBANNE ¹⁾

has assessed and evaluated the product under system 3 and issued the following report:

99-452 to 99-467 ¹⁾

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance


Harmonized technical specification according to EN 442-1:2014

Essential characteristics	Performance
Reaction to fire	A1
Release of dangerous substances	None
Maximal operating pressure (MOP)	400 kPa ¹⁾
Pressure tightness: - Resistance to pressure at 1,30 x MOP: - Resistance to pressure at 1,69 x MOP	no leakage no breakage
Surface temperature maximum	120 °C
Resistance to pressure	Pass (520 kPa) ¹⁾
Rated thermal outputs	$\phi 30 = 665 \text{ W}$ ¹⁾
	$\phi 50 = 1301 \text{ W}$ ¹⁾
Thermal output in different operating conditions (characteristic curve)	$\phi = 7,62 \times \Delta T t^{1,3140}$ ¹⁾
Durability as: - Resistance against corrosion: - Resistance against minor impact:	no corrosion after 100 h humidity Class 0

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Remark ¹⁾: These are example values. The actual values of all products covered by this declaration can be found on the product packaging labels, in technical documentations and in digital medias.

Vaux-Andigny, le 15/09/2017



Zehnder group Vaux-Andigny

17, Rue des Parachutistes de la France Libre

BP 1 - 02110 VAUX-ANDIGNY

Tél. + 33 3 23 66 88 00 - Fax + 33 3 23 66 88 17

RCS Saint-Quentin 428 287 049 - APE : 2521 Z

Code UE : FR 32 428 287 049