nVent CADDY Speed Link SLS



FEATURES GUIDE

SAFETY FEATURES

Length of stem allows the device to be installed in strut profiles without the need to insert fingers or tools into the strut

UL Listing on all 4 end fittings for pre-cut lengths

Two jaws grip the wire inside the device, holding the wire more securely than single-cam devices common among most competitors

Keyless release tube is designed to allow safe and easy adjustment, even while wearing bulky gloves

The color of the line corresponds to the larger goal of each feature:

SAFETY FEATURES AESTHETICAL FEATURES

EASE OF USE FEATURES



AESTHETICAL FEATURES

Low profile locking device provides a positive aesthetic to a finished project



Similar housing style creates a consistent look when used in projects alongside the Speed Link SLK System

EASE OF USE FEATURES

"Push-to-install" retaining nut simplifies installation

Engineered elongated retaining nut reduces unwanted sway of the trapeze during installation and provides higher stability

The outside of the housing is threaded for easy and secure attachment to the nut

nVent CADDY Speed Link is lighter, faster to install, easier to transport and generates less waste than alternative hanging methods

Two tool-free locking devices are available for three wire sizes:

- SLS2 compatible with 1.5mm and 2mm wire
- SLS3 compatible with 3mm wire

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

nproper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and/or death, and void your warranty.

©2018 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners nVent reserves the right to change specifications without notice