

nVent CADDY Speed Link SLK with Nail Gun Bracket, 1.5 mm Wire, 3 m Length

CATALOG NUMBER

SLK15L3GBSF



FEATURES

Complete system includes wire, locking device and concrete nail gun insert bracket

Clips onto nozzle of gas or battery-actuated nail guns allowing for hands-off installation at structure or from the floor using a pole

Longer leg angle bracket for tool clearance

Quickly and easily attaches to concrete, steel or composite metal decking

PRODUCT ATTRIBUTES


Article Number: 197813 Material: Steel;Zinc Alloy;Polypropylene;Nylon Finish: Electrogalvanized Static Load Safety Factor: 5:1 Complies With: SMACNA HVAC-DCS Wire Rope Diameter: 1.5 mm Wire Rope Length: 3m A: 38 mm B: 25.5 mm Static Load: 195N Height (H): 55 mm

ADDITIONAL PRODUCT DETAILS

Static Load represents the static load of the nail gun insert assembly. Please consult with the nail manufacturer to evaluate the static load of the nail and type of concrete used for the installation. Maximum load is the lesser of the static load from the nail manufacturer or the published load for the assembly.

Nail gun insert is compatible with BeA® CN60-688ES, Hilti® BX 3, GX 3, DEWALT® Trak-It C3, SPIT® PULSA 40E, 800E, 700, 1000 or equivalent nailers.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



This document is system-generated.