


# MFD

## nVent CADDY Macrofix Insulated M8/M10

Part Number	Article Number	Pipe Range	Rod Size	Wrench size for M8/M10	Wrench size for M6 screw	Tightening torque for M6 screw	RAL Product Load Rating *
MFD015	586001	11 – 15 mm, 8 DN	M8/M10	13mm	10mm	2 Nm	1,000 N
MFD019	586002	15 – 19 mm, 10 DN					
MFD025	586003	19 – 25 mm, 15 DN					
MFD031	586004	25 – 31 mm, 20 DN					
MFD037	586005	31 – 37 mm, 25 DN					
MFD044	586006	37 – 44 mm, 32 DN					1,500 N
MFD050	586007	44 – 50 mm, 40 DN					
MFD058	586008	50 – 58 mm					
MFD068	586009	58 – 68 mm, 50 DN					
MFD078	586010	68 – 78 mm, 65 DN					
MFD088	586011	78 - 88 mm					2,000 N
MFD098	586012	88 – 98 mm, 80 DN					
MFD108	586013	98 – 108 mm, 90 DN					
MFD118	586014	108 - 118mm, 100 DN					
MFD128	586015	118 - 128 mm					
MFD138	586016	128 - 138 mm					3,000 N
MFD148	586017	138 - 148 mm, 125 DN					
MFD160	586018	150 - 160 mm					
MFD170	586019	160 - 170 mm, 150 DN					
MFD200	586020	190 - 200 mm					
MFD215	586021	205 - 215 mm					3,600 N
MFD225	586022	215 - 225 mm, 200 DN					
MFD250	586023	239 - 250 mm					
MFD275	586024	265 - 275 mm, 250 DN					
MFD319	586025	309 - 319 mm					4,000 N

\* RAL Product Load Rating per RAL-GZ 655.



#### WARNING:

1. nVent products shall be installed and used only as indicated in nVent product instruction sheets and training materials. Instruction sheets are available at [www.nVent.com](http://www.nVent.com) and from your nVent customer service representative.
2. nVent products must never be used for a purpose other than the purpose for which they were designed or in a manner that exceeds specified load ratings.
3. All instructions must be completely followed to ensure proper and safe installation and performance.
4. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and/or death, and void your warranty.
5. Products that are manufactured using spring steel components shall be used only in a non-corrosive indoor environment.
6. All pipe supports, hangers, intermediate components and structural attachments must ONLY be used as described herein and are NEVER to be used for any other purpose.

NOTE: All load ratings are for static conditions and do not account for dynamic loading such as wind, water or seismic loads, unless otherwise noted.

The customer is responsible for:

- a. Conformance to all governing codes.
- b. The integrity of structures to which the products are attached, including their capability of safely accepting the loads imposed, as evaluated by a qualified engineer.
- c. Using appropriate industry standard hardware as noted above.

#### SAFETY INSTRUCTIONS:

All governing codes and regulations and those required by the job site must be observed. Always use appropriate safety equipment such as eye protection, hard hat, and gloves as appropriate to the application.

nVent, nVent CADDY, nVent ERICO Cadweld, nVent ERICO Critec, nVent ERICO, nVent ERIFLEX, and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

TECHNICAL SUPPORT:  
[www.nVent.com](http://www.nVent.com)

CFS552\_D

1 OF 2

© 2016-2019 nVent All Rights Reserved



