### **TUNGSRAM**

Innovation is our heritage EST. 1896





### Integrated Bulkhead LED Bulkhead G1 TU D25 17W 840 S NNN

93107555

### **Product information**

A simple and elegant light fitting, designed with Integrated LED Light Module and dedicated optic, both for interior and exterior applications. The Integrated Bulkhead range offers a comprehensive choice of versions including two sizes, opal diffuser and optional sensor function. It is a wall and ceiling LED luminaire that can be utilised in versatile application ranges including damp environments, entrance halls, receptions, stairwells, corridors, circulation routes, rest areas and outside walls of buildings.



# Integrated Bulkhead LED Bulkhead G1 TU D25 17W 840 S NNN 93107555

### Product data

Product code	93107555
Description	LED Bulkhead G1 TU D25 17W 840 S NNN
DIALux description	TUNGSRAM - Integrated Bulkhead - 1600lm - 17W - 4000K - 80CRI - 93107555[SKU] - Surface
Brand	TUNGSRAM
Product category	Integrated Bulkhead
Product family	Bulkheads
Application areas	Stairways / Corridors
DUN Code	10064894579186
Light source	LED
Sensor	No sensor
Emergency option	No EM
Mounting type	Surface
Weight [kg]	0,7
Body color	White
Product dimensions (Length) x (Width) x (Height) [mm]	Dia 250 x Dia 250 x 102
Operating temperature min [°C]	-30
Operating temperature max [°C]	40
Rated ambient temperature (tq) [°C]	25
Cooling	Passive
Certifications	CE
General warranty [year]	5



# Integrated Bulkhead LED Bulkhead G1 TU D25 17W 840 S NNN 93107555

#### Performance data

System power [W]	17
Nominal luminous flux [lm]	1600
Rated efficacy [lm/W]	94
Rated life L70/B50 [h]	60000
IP front (optical)	65
IP back (electrical)	65
IP Rating	65
Impact resistance (IK)	IK10

#### Photometrical data

Photometric distribution	Wide
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	>=80
Nominal beam angle [°]	125 ± 12
UGR value (4H8H)	26,1
Colour consistency in MacAdam steps SDCM	≤6

#### Electrical data

IEC protection class	Class II
Operating voltage [V]	220-240V
Rated frequency or frequency range [Hz]	50/60Hz
Lamp input current [mA]	84
Nominal lamp power factor	>=0.9
Controllability	Static





## Integrated Bulkhead LED Bulkhead G1 TU D25 17W 840 S NNN 93107555


#### Logistic data

Box quantity	1
Shipment	Standard
Product status	Available

#### Light distribution







#### **Downloads & Links**

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation guide (PDF)

Images (HTTP)

Photometry files for EMERGENCY versions (HTTP)

DoC document (PDF)

Datasheet (HUN) (PDF)

Datasheet (FR) (PDF)