

Innovation is our heritage EST. 1896





IP20 Diffuser downlight LED DLR Diff P1 TU6 IP20 15W 840 SST 93107534

Product information

Tungsram introduces the new standard range of LED Diffuser Downlighters. There are a selection of sizes and colour temperature options to meet customer requirements. With this new range, lighting can be upgraded in key segments such as offices, commercial buildings, retail back of house areas and hospitality.



IP20 Diffuser downlight LED DLR Diff P1 TU6 IP20 15W 840 SST 93107534

Product data

93107534
LED DLR Diff P1 TU6 IP20 15W 840 SST
TUNGSRAM - IP20 Diffuser downlight - 1500lm - 15W - 4000K - 80CRI - 93107534[SKU] - Recessed
TUNGSRAM
Diffuser Downlight IP20
Downlighters
Public building, Office, Retail
10064894568579
LED
No sensor
No EM
Recessed
0,32
White
Dia 180 x Dia 180 x 81
-10
40
25
Passive
CE, EAC
5

Performance data

System power [W]	15
Nominal luminous flux [lm]	1500
Rated efficacy [lm/W]	100
Rated life L70/B50 [h]	45000
IP front (optical)	20
IP back (electrical)	20
IP Rating	20
Energy efficiency class (EEC)	F

Photometrical data

Photometric distribution	Very Wide Flood
Nominal correlated colour temperature (CCT) [K]	4000
Colour rendering index (CRI) [Ra]	>=80
Nominal beam angle [°]	100 ± 15
UGR value (4H8H)	27,1
Colour consistency in MacAdam steps SDCM	≤6
Photobioligical risk	RG1

Electrical data

IEC protection class	Class II
Operating voltage [V]	220-240V
Rated frequency or frequency range [Hz]	50/60Hz
Lamp input current [mA]	75
Nominal lamp power factor	>=0.9
Controllability	Static





IP20 Diffuser downlight LED DLR Diff P1 TU6 IP20 15W 840 SST 93107534


Logistic data

Box quantity	1
Shipment	Standard
Product status	Available

Light distribution







Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation guide (PDF)

Images (HTTP)

DoC Document (PDF)

Datasheet (FR) (PDF)