



9

kWh/1000h

94

lumens/watt

LED Stik

LED 9/STIK/840/220-240V/E27/BX TU
93110185

Product information

LED Stik illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years*. That's a long time you can spend not worrying about light bulbs.

Features & benefits

- LED technology for energy saving
- Redesigned shape with multiple advantages:
- To fit in more fixtures compared to CFL
- Optimised for omni-directional light distribution
- Space-saving benefits on-shelf
- 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W bulb
- Rated life of 15 years*
- 3 colour options - 3000K, 4000K & 6500K
- Always ready - instant brightness
- No mercury - worry-free use and disposal
- Warranty: 2 years with maximum 8 000 burning hours

according to Tungsram Standard Warranty
conditions

- Based on 2.7 hours of per day use.
-

Product data

| | |
|------------------------------------|----------|
| Product Code | 93110185 |
| Bulb Shape | T38 |
| Bulb Finish | White |
| Bulb maximum overall diameter [mm] | 38 |
| Nominal Length [mm] | 115.5 |
| Net weight per piece [g] | 41 |
| Dimmability | No |
| RoHS compliant | Yes |
| Brand | Tungsräm |
| Cap/Base | E27 |

Performance data

| | |
|---|-------|
| Nominal/ Rated Beam Angle [°] | 240 |
| Rated Lumens [lm] | 850 |
| Weighted energy consumption [kWh/1000h] | 9.0 |
| Rated efficacy [lm/W] | 94.4 |
| Energy efficiency class (EEC) | F |
| Rated life L70/B50 [h] | 15000 |
| Nominal correlated colour temperature (CCT) [K] | 4000 |
| Nominal lumens [lm] | 850 |
| Colour Rendering Index (CRI) [Ra] | 80 |


Electrical data

| | |
|---|------------|
| Operating Temperature (MIN) [°C] | -20°C |
| Operating Temperature (MAX) [°C] | +40°C |
| Starting time (sec) | <0,5 s |
| Power Factor | >0.5 |
| Warm up time up to 60% of full light output | Instant on |
| Number of switching cycles | 50k |
| Nominal lamp voltage range [V] | 220-240V |
| Nominal power [W] | 9 |

Logistic data

| | |
|----------------|----------------|
| Shipment | Standard |
| DUN Code | 15994100027321 |
| EAN Code | 5994100027324 |
| Pack Quantity | 15 |
| Product status | Available |

Light distribution



Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Photometry \(IES\)](#)

[Datasheet \(PDF\)](#)

[Images \(HTTP\)](#)

[DoC document \(PDF\)](#)

[DoC document - E14 \(PDF\)](#)

