TUNGSRAM

Innovation is our heritage EST. 1896





Spotlight G1 5W

LED Spotlight G1 TU WRF IP65 5W 830 s

93100528

Product information

The Tungsram Recessed Spotlight G1 5W range has functional and minimalistic design with fix and adjustable versions. These LED Spotlights are ideal for small areas to make your ceilings seem higher, or when you are looking for directional lighting. Never was the installations easier and quicker with these products. The Recessed Spotlight G1 5W range offers all the benefits of LED lighting to our customers – fresh light quality, reduced energy consumption and less maintenance.



Spotlight G1 5W LED Spotlight G1 TU WRF IP65 5W 830 S 93100528

Product data

DescriptionLED Spotlight G1 TU WRF IP65 5W 830 SDIALux descriptionTUNGSRAM - Spotlight G1 5W - 380lm - 5W - 3000K - 80CRI - 93100528[SKU] - RecessedBrandTUNGSRAMProduct categoryRecessed Spotlight 5WProduct familyDownlightersApplication areasHospitality, Offices, ResidentialLight sourceLEDSensorNo sensorEmergency optionNo EMMounting typeRecessedWeight [kg]0,11Body colorWhite, RAL9003	Product code	93100528
Brand TUNGSRAM Product category Recessed Spotlight 5W Product family Downlighters Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,11	Description	LED Spotlight G1 TU WRF IP65 5W 830 S
Product category Product family Downlighters Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,11	DIALux description	
Product family Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option Mounting type Recessed Weight [kg] Downlighters Hospitality, Offices, Residential LED No sensor Recessed	Brand	TUNGSRAM
Application areas Hospitality, Offices, Residential Light source LED Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,11	Product category	Recessed Spotlight 5W
Light source Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,11	Product family	Downlighters
Sensor No sensor Emergency option No EM Mounting type Recessed Weight [kg] 0,11	Application areas	Hospitality, Offices, Residential
Emergency option No EM Mounting type Recessed Weight [kg] 0,11	Light source	LED
Mounting type Recessed Weight [kg] 0,11	Sensor	No sensor
Weight [kg] 0,11	Emergency option	No EM
	Mounting type	Recessed
Body color White, RAL9003	Weight [kg]	0,11
	Body color	White, RAL9003
Product dimensions (Length) x (Width) x (Height) Dia 85 x Dia 85 x 54 [mm]	. 9 / . , .	Dia 85 x Dia 85 x 54
Operating temperature min [°C] -10	Operating temperature min [°C]	-10
Operating temperature max [°C] 40	Operating temperature max [°C]	40
Rated ambient temperature (tq) [°C] 25	Rated ambient temperature (tq) [°C]	25
Cooling Passive	Cooling	Passive
Certifications CE	Certifications	CE
General warranty [year] 3	General warranty [year]	3

Performance data

System power [W]	5
Nominal luminous flux [lm]	380
Rated efficacy [lm/W]	76
Rated life L70/B50 [h]	20000
IP front (optical)	65
IP back (electrical)	65
IP Rating	65

Photometrical data

Photometric distribution	Narrow Flood
Nominal correlated colour temperature (CCT) [K]	3000
Colour rendering index (CRI) [Ra]	>=80
Nominal beam angle [°]	36
UGR value (4H8H)	21,1
Colour consistency in MacAdam steps SDCM	≤4
Photobioligical risk	RG0


Electrical data


IEC protection class	Class II
Operating voltage [V]	220-240V
Rated frequency or frequency range [Hz]	50/60Hz
Lamp input current [mA]	50
Nominal lamp power factor	>=0.5
Controllability	Static


Logistic data

Box quantity	1
Shipment	Standard
Product status	Available

Light distribution







Downloads & Links

Go to the catalog site (HTTP)

Datasheet (PDF)

Installation guide (PDF)

Images (HTTP)

DoC Document (PDF)

Dimmer Compatibility List (PDF)

Datasheet (HU) (PDF)

Datasheet (FR) (PDF)