TUNGSRAM

Innovation is our heritage EST. 1896





Tulox XO Tubular Clear LU150/100/XO/T/E40 TU 93102237

Product information

Tulox XO High Pressure Sodium lamps offer outstanding luminous efficacy, lumen maintenance and long life, thus reducing energy and maintenance costs.

Application areas



 $(\bigcap \mathbb{N})$ Road and tunnel



Street and pedestrian



(M) Commercial areas



Tulox XO Tubular Clear LU150/100/XO/T/E40 TU 93102237

Product data

Product Code	93102237
Light Center Length [mm]	133
Bulb Shape	Tubular
Bulb Finish	Clear
Maximum Overall Length [mm]	211
Net weight per piece [g]	143
Gross weight per piece [g]	178
Operating position	U - Universal
Mercury Content [mg]	13.3
Brand	Tungsram
Cap/Base	E40

Performance data

Rated Lumens [lm]	17600
Weighted energy consumption [kWh/1000h]	168.3
Nominal efficacy [LpW]	117
Rated efficacy [LpW]	115
Energy efficiency class (EEC)	F
Avarage rated life	45.000 hrs
Nominal chromaticity coordinate X	0.53
Nominal chromaticity coordinate Y	0.43
Nominal correlated colour temperature (CCT) [K]]	2100
Nominal lumens [lm]	17500
Colour Rendering Index (CRI) [Ra]	25



Tulox XO Tubular Clear LU150/100/XO/T/E40 TU 93102237

Electrical data

Rated power [W]	153.0
Lamp Current [A]	1.8
Design Ambient Temperature [°C]	25
Run-up time (sec)	240
Hot restart time (sec)	240
Dimming Capability	Yes
Ballast Required	Yes
Nominal power [W]	150
Nominal lamp voltage [V]	100


Logistic data

DUN Code 1	5994100017636
EAN Code 5	994100017639
Pack Quantity 1	2
Layer quantity 2	288 EUR, 372 UK
Layer quantity EUR 2	288
Layer quantity UK 3	372
Pallet quantity EUR (PC) 8	364
Pallet quantity UK (PC)	116
Outer case size 2	215 x 162 x 284 (mm)
Product status A	Available

Lumen maintenance data



Survival data



Downloads & Links

Go to the catalog site (HTTP)

Product datasheet (PDF)

Datasheet (PDF)

High-res images / Technical drawings (HTTP)

