Presslok™ Splice Connectors U1R, Box

Part Number:
U1R-BOX

With the Presslok™ series of tools and connectors, service providers can meet the demand for enhanced customer services such as high-speed internet, video-on-demand, and video conferencing. Presslok connectors also offer full wire-range capability, increased port size to accommodate up to 2.08 mm (0.082 in) insulation sizes, and solvent resistant plastic construction. As new technologies migrate into the local loop, the importance of reliable connections in the embedded plant has increased exponentially. Each connection is a potential point of failure in high-bandwidth applications, which could require additional time and expense for a technician to repair. That is where the full line of Presslok connectors can really make a difference.

Features and Benefits

Fast installation

Ease of Use

Wide Range of Common Wire Guages

Factory-installed sealant

Dry versions available for Central Offices and Vaults



Presslok™ Splice Connectors, U1R Gel-filled IDC Inline Drop Splice Connector, Box Packaging (100 pce)

Presslok™ Splice Connectors U1R, Box

Specifications

General Specifications	
Product type	Copper Splice Connector

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Composition	Gel-filled
No. of connections	Two (2)
Connector type	Inline Drop
Conductor	AWG 24 - 19
Conductor Range	0.5 mm to 0.9 mm

Dimensions	
Weight	0.08 kg

Ordering Information	
Product Number	U1R-BOX
Packaging method	Box
Units per delivery	1000/1

RoHS COMPLIANT

Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
00 800 2676 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2026 Corning Optical Communications. All rights reserved.