

Everon™ Copper Datacom Class EA Patch Cord, 2xRJ45, Cat.6A, S/FTP LSZH™ AWG 30 grey, 1 m

CORNING

Référence du produit: MCAAWB-G1002-A010-V0

The application-neutral Everon™ Copper Datacom category 6A patch cords have four individual foil-shielded pairs (PiMF) and an additional braid shield (S/FTP). They are assembled with a shielded RJ45 connectors on each end. The zero halogen patch cords (LSZH™) are non-corrosive according to IEC 60754-2 (FRNC), low smoke according to IEC 61034 and flame retardant according to IEC 60332-1. Everon Copper Datacom MCAAWB patch cords provide additional latch protection. They are available in various lengths and colours.

Caractéristiques et Avantages

Application-neutral due to using all four pairs of RJ45 connectors

Outstanding transmission characteristics according to 10GBase-T

Additional latch protection

Category 6A

Supports Power over Ethernet (PoE / PoE+) according IEEE 802.3at



Everon™ Copper Datacom Class EA Patch Cord, 2xRJ45, Cat.6A, S/FTP LSZH™ AWG 30 grey, 1 m

CORNING

Spécifications

General Specifications

Area/range of application	1000Base-T; 2,5GBase-T; 5GBase-T; 10GBase-T/FDDI; ATM
Cable assembly type	Patch cords
Environment	Indoor
Category	6A
Cable type	S/FTP
Halogen-free	Yes
Brand	Everon®
Third Party Certificate	Yes (www.corning.com/emea/en/certificates)

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Design And Test Criteria	Compliant with PoE / PoE++ IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt

Environmental Conditions

Temperature range, installation	0 °C - 50 °C
Temperature range, operation	-20 °C - 60 °C
Transport and indoor storage	Dry environment, no direct sunlight, room temperature ≤ 40 °C

Cable Design

Twisting	2 cores to a pair
Pair screen	Al-laminated foil around each pair
Overall screen	Copper braid, tinned
Outer jacket material	LSZH/FRNC
Outer jacket colour	Grey

Everon™ Copper Datacom Class EA Patch Cord, 2xRJ45, Cat.6A, S/FTP LSZH™ AWG 30 grey, 1 m

CORNING

Mechanical Specifications

Fire load	0.329 MJ/m
Min. bend radius installation	34 mm

Specifications - Connector A

Connector type	RJ45 - 8/8
Durability Cycles	750 N/A
Connector Material	Pin gold plated 50μ inch

Specifications - Connector B

Connector type	RJ45 - 8/8
Durability Cycles	750 N/A
Connector Material	Pin gold plated 50μ inch

Electrical Specifications

Mutual capacity	1600 pF/km
Max. loop resistance	381 Ω/km
Propagation delay	5.38 ns/m at 100 MHz
DC resistance unbalance	4 %
Insulation resistance	500 MΩ*km
Impedance Zo at 1-100 MHz	100 Ω ± 5% at 100 MHz

Ordering Information

Référence du produit	MCAAWB-G1002-A010-V0
Code EAN	4059496920268
Weight	3 kg
Packaging method	Corn Starch Bag

Everon™ Copper Datacom Class EA Patch Cord, 2xRJ45, Cat.6A, S/FTP LSZH™ AWG 30 grey, 1 m

CORNING

Ordering Information

Shipping weight	0.04 kg
Units per delivery	1/1



Corning Optical Communications GmbH & Co. KG • Lelziger Strasse 121 • 10116 Berlin, Allemagne
+33(0)24000 2184 ou +33(0)2 4000 2185 • FAX: +49 30 5303 2335 • <https://www.corning.com/opcomm/emea/fr>

Une liste complète des marques déposées de Corning Optical Communications est disponible à www.corning.com/opcomm/emea/trademarks. Corning Optical Communications est certifié selon la norme ISO 9001 et ISO 14001. © 2023 Corning Optical Communications. Tous droits réservés.