Presslok™ Splice Connectors U1R, Box



Part Number: U1R-BOX

With the Presslok™ series of tools and connectors, service providers can meet the demand for enhanced customer services such as high-speed internet, video-on-demand, and video conferencing. Presslok connectors also offer full wire-range capability, increased port size to accommodate up to 2.08 mm (0.082 in) insulation sizes, and solvent resistant plastic construction. As new technologies migrate into the local loop, the importance of reliable connections in the embedded plant has increased exponentially. Each connection is a potential point of failure in high-bandwidth applications, which could require additional time and expense for a technician to repair. That is where the full line of Presslok connectors can really make a difference.

Features and Benefits

Fast installation

Ease of Use

Wide Range of Common Wire Guages

Factory-installed sealant

Dry versions available for Central Offices and Vaults



$\textbf{Presslok}^{\text{\tiny{TM}}} \textbf{ Splice Connectors U1R, Box}$



Specifications

General Specifications	
Product type	Copper Splice Connector

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Composition	Gel-filled
No. of connections	Two (2)
Connector type	Inline Drop
Conductor	AWG 24 - 19
Conductor Range	0.5 mm to 0.9 mm

Dimensions	
Weight	0.08 kg

Ordering Information	
Product Number	U1R-BOX
EAN Code	4059496712993
Packaging method	Вох
Units per delivery	1000/1

Presslok™ Splice Connectors U1R, Box





Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany +00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2024 Corning Optical Communications. All rights reserved.