

Fiche produit

Article n° 04.410.0981.0

Marquage des manchons, bouton-pression WMS
304/15



Article n°	04.410.0981.0
EAN	4049088379635
Unité de commande	500 Piece(s)

certificats/approbations

Données techniques

général

Longueur	15 mm
matériel	Plastique
Impression	Aucun
Méthode de montage	encliquetable
Model	Marquage tag
Model	Marquage tag
Impression	Aucun
matériel	Plastique
Diamètre du câble	8 mm
Diamètre du câble max.	10 mm
Longueur	15 mm
Avec champ de description	Oui
Méthode de montage	encliquetable
Transparent	Oui
Auto-adhésif	Aucun
Magnetic	Aucun

Dessin technique

1	2	3	4	5	6																									
These dimensions are for specially checked delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use <table border="1"> <thead> <tr> <th>Teilenummer / part no.</th> <th>Typ / type</th> <th>für Leitungsdurchmesser D (mm) / for Cable Diameter D (mm)</th> <th>Länge L (mm) / Length L (mm)</th> <th>Hülsen pro Packung / Sleeves per pack</th> </tr> </thead> <tbody> <tr> <td>04.410.0681.0</td> <td>WMS 301/15</td> <td>2,0 - 3,5</td> <td>15</td> <td>1000</td> </tr> <tr> <td>04.410.0781.0</td> <td>WMS 302/15</td> <td>2,8 - 5</td> <td>15</td> <td>1000</td> </tr> <tr> <td>04.410.0881.0</td> <td>WMS 303/15</td> <td>5 - 8</td> <td>15</td> <td>500</td> </tr> <tr> <td>04.410.0981.0</td> <td>WMS 304/15</td> <td>8 - 10</td> <td>15</td> <td>500</td> </tr> </tbody> </table>						Teilenummer / part no.	Typ / type	für Leitungsdurchmesser D (mm) / for Cable Diameter D (mm)	Länge L (mm) / Length L (mm)	Hülsen pro Packung / Sleeves per pack	04.410.0681.0	WMS 301/15	2,0 - 3,5	15	1000	04.410.0781.0	WMS 302/15	2,8 - 5	15	1000	04.410.0881.0	WMS 303/15	5 - 8	15	500	04.410.0981.0	WMS 304/15	8 - 10	15	500
Teilenummer / part no.	Typ / type	für Leitungsdurchmesser D (mm) / for Cable Diameter D (mm)	Länge L (mm) / Length L (mm)	Hülsen pro Packung / Sleeves per pack																										
04.410.0681.0	WMS 301/15	2,0 - 3,5	15	1000																										
04.410.0781.0	WMS 302/15	2,8 - 5	15	1000																										
04.410.0881.0	WMS 303/15	5 - 8	15	500																										
04.410.0981.0	WMS 304/15	8 - 10	15	500																										
These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use <table border="1"> <thead> <tr> <th>Teilenummer / part no.</th> <th>Typ / type</th> <th>Abmessungen L x H (mm) / Dimensions L x H (mm)</th> </tr> </thead> <tbody> <tr> <td>04.410.1081.2</td> <td>WMS SI2K02W/15N</td> <td>15x4</td> </tr> <tr> <td>04.410.1081.8</td> <td>WMS SI2K02Y/15N</td> <td>15x4</td> </tr> </tbody> </table>						Teilenummer / part no.	Typ / type	Abmessungen L x H (mm) / Dimensions L x H (mm)	04.410.1081.2	WMS SI2K02W/15N	15x4	04.410.1081.8	WMS SI2K02Y/15N	15x4																
Teilenummer / part no.	Typ / type	Abmessungen L x H (mm) / Dimensions L x H (mm)																												
04.410.1081.2	WMS SI2K02W/15N	15x4																												
04.410.1081.8	WMS SI2K02Y/15N	15x4																												
These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use <table border="1"> <thead> <tr> <th colspan="2">Technical Specifications</th> </tr> </thead> <tbody> <tr> <td>Material</td> <td>PVC</td> </tr> <tr> <td>Flammability</td> <td>UL - 94 Class V0</td> </tr> <tr> <td>Temperature range</td> <td>-15 to +70 °C</td> </tr> <tr> <td>Resistance to UV</td> <td>UNI EN ISO 4892-2:2006</td> </tr> <tr> <td>Color</td> <td>transparent / white</td> </tr> </tbody> </table>						Technical Specifications		Material	PVC	Flammability	UL - 94 Class V0	Temperature range	-15 to +70 °C	Resistance to UV	UNI EN ISO 4892-2:2006	Color	transparent / white													
Technical Specifications																														
Material	PVC																													
Flammability	UL - 94 Class V0																													
Temperature range	-15 to +70 °C																													
Resistance to UV	UNI EN ISO 4892-2:2006																													
Color	transparent / white																													
These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use <table border="1"> <thead> <tr> <th colspan="2">Tolerierung Size ISO 14445 E / tolerance system Size ISO 14445 E</th> </tr> </thead> <tbody> <tr> <td>Freibleierversion nach general tolerance</td> <td>CAD - Zeichnung, keine manuelle Änderungen CAD drawing no manual modifications allowed</td> </tr> <tr> <td>Material</td> <td>2016 Tag/Date Name gezeichnet 25.10. ScA</td> </tr> <tr> <td>Vol.</td> <td>mm³ Off./surf. mm² Ersatz für / replacement for</td> </tr> <tr> <td>Index</td> <td>Datum / Blatt date sheet</td> </tr> <tr> <td>Änderung / revision</td> <td>www.wieland-electric.com</td> </tr> </tbody> </table>						Tolerierung Size ISO 14445 E / tolerance system Size ISO 14445 E		Freibleierversion nach general tolerance	CAD - Zeichnung, keine manuelle Änderungen CAD drawing no manual modifications allowed	Material	2016 Tag/Date Name gezeichnet 25.10. ScA	Vol.	mm³ Off./surf. mm² Ersatz für / replacement for	Index	Datum / Blatt date sheet	Änderung / revision	www.wieland-electric.com													
Tolerierung Size ISO 14445 E / tolerance system Size ISO 14445 E																														
Freibleierversion nach general tolerance	CAD - Zeichnung, keine manuelle Änderungen CAD drawing no manual modifications allowed																													
Material	2016 Tag/Date Name gezeichnet 25.10. ScA																													
Vol.	mm³ Off./surf. mm² Ersatz für / replacement for																													
Index	Datum / Blatt date sheet																													
Änderung / revision	www.wieland-electric.com																													
These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use These marks indicate the location of delivery only respecting dimensions with E marked dimensions are only valid for internal use <table border="1"> <thead> <tr> <th colspan="2">MARKIERHUELSE Marking Sleeve</th> </tr> </thead> <tbody> <tr> <td>04.410.0681.0 01K</td> <td></td> </tr> </tbody> </table>						MARKIERHUELSE Marking Sleeve		04.410.0681.0 01K																						
MARKIERHUELSE Marking Sleeve																														
04.410.0681.0 01K																														