

A top-down view of a 24-pin connector. The pins are arranged in two rows of 12. The top row is numbered 1 through 12 from left to right. The bottom row is numbered 13 through 24 from left to right. The connector has a central body with two side flaps, each featuring a latch mechanism. The entire unit is mounted on a base with four screws at the corners.

Teile-Nr. part no.	Typ type	Polzahl pole	L	l
70.300.0640.0	BAS BUS 6 2,5 50	6x	49,8	44
70.300.1040.0	BAS BUS 10 2,5 50	10x	62,8	57
70.300.1640.0	BAS BUS 16 2,5 50	16x	83,3	77,5
70.300.2440.0	BAS BUS 24 2,5 50	24x	109,8	104

Tolerierung Size ISO 14405 ☺ / Tolerance system Size ISO 14405 ☺ (This ISO-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances).										ja/yes ☑ Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten. Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared!																			
Freitoleranz nach General tolerance					CAD - Zeichnung, keine manuellen Änderungen CAD - drawing, no manual modifications allowed					1. Verwendung: First Use:					Blatt: 1 von 1 Sheet: 1 of 1														
		/		Werkstoff / Material						Tag/Date			Name					T	Zeichnung Nr. / Drawing No.										Index
		/							gezeichnet drawn	19.07.2022			Lunz S.																
		/							Elektronische Freigabe Electronic Release																				
		/																											
		/	Maßstab / Scale 1:1	Maße in mm / Dimensions are in mm																									
		/																											
		/	Vol.	mm³		Öfl./Srf.		mm²		Ersatz für / Replacement for: 70.300.0640.001K mit Index "c" vom 31.01.2017																			
		/	 wieland							Type		Benennung/Title BUCHSENEINSATZ 2,5 qmm 500V 16A Schraubanschluss u. Drahtschutz female insert screw connection and wire protection																	
		/																											
		/																											
		/																											
Index	Datum / Blatt Date / Sheet									siehe Tabelle																			
Änderung / Revision																													