

# 64662 300 W 240 V

Halogen (>  $130\ V$ ) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets



#### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift







## Product datasheet

### Technical data

### **General Product Information**

ANSI code	-
LIF code	M/38
Global order reference	64662


### **Electrical Data**

Nominal wattage	300 W
Nominal voltage	240 V

### **Photometric Data**

Nominal luminous flux	5000 lm
Useful luminous flux (Φuse)	5275 lm
Φuse value refers to luminous flux	360
Illuminated field	9.0*11.0 mm²
Color temperature	2900 К
Correlated color temperature CCT	2910 K
Chromaticity coordinate x	0.444
Chromaticity coordinate y	0.407
Color rendering index Ra	100

## **Physical Attributes & Dimensions**



Lamp base	GY9.5
Diameter	17.5 mm
Length	80.0 mm
Product weight	18.80 g

## **Operating Conditions**

## Product datasheet

Burning position	Any
Dimmable	Yes

### **Lifetime Data**

Nominal lifetime	2000 hr
Nominal metime	2000 111

## **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier 4052899144248			
Energy efficiency class	G		
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1 No declarable substances contained			

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899144248	64662 300 W 240 V	Folding carton box 1	42 mm x 42 mm x 111 mm	0.20 dm <sup>3</sup>	35.00 g
4052899144255	64662 300 W 240 V	Shipping carton box 12	180 mm x 140 mm x 127 mm	3.20 dm <sup>3</sup>	486.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.