

# 64748XS 1000W 240V

Halogen (>  $130\ V$ ) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets



#### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift



## Product datasheet

#### Technical data

## **General Product Information**

Product number (Americas)	55039	
<b>Product name (Americas)</b> 64748 XS 1000W 240V 12/CS 1/SKU		
ANSI code	-	
Global order reference	64748 XS 1000W	

### **Electrical Data**

Nominal wattage	1000 W
Nominal voltage	240 V

### **Photometric Data**

Nominal luminous flux	25000 lm
Useful luminous flux (Φuse)	23920 lm
Φuse value refers to luminous flux	360
Color temperature	3200 K
Correlated color temperature CCT	3121 K
Chromaticity coordinate x	0.428
Chromaticity coordinate y	0.401
Color rendering index Ra	100

# **Physical Attributes & Dimensions**

Lamp base	GY9.5
Diameter	22.2 mm
Length	95.0 mm
Filament	C13-D
Product weight	31.50 g

# **Operating Conditions**

Burning position	S180
Dimmable	Yes

### **Lifetime Data**

Nominal lifetime	250 hr

## **Environmental & Regulatory Information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

# Product datasheet

Primary article identifier 4052899545380	
Energy efficiency class G	
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

### Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899545380	64748XS 1000W 240V	Folding carton box 1	40 mm x 40 mm x 128 mm	0.20 dm <sup>3</sup>	54.00 g
4052899545397	64748XS 1000W 240V	Shipping carton box 12	177 mm x 136 mm x 152 mm	3.70 dm <sup>3</sup>	854.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.