Product datasheet



Product features and benefits

- Lightweight and compact reflector lamps with ECG
- High luminance through very short arc and high pressure
- Produces brilliant light effects
- Stable light output over the entire lifetime
- Long lifetime
- Easy lamp replacement
- Approved by leading moving lighting fixture companies





Technical data

General Product Information

Product number (Americas)	54750	
Product name (Americas)	SIRIUS HRI 140W RO 2/CS 1/SKU	
Family brand	SIRIUS HRI	
Category	CUSTOMIZED	
Global order reference	SIRIUS HRI 140 W RO	


Electrical Data

Nominal wattage	140 W
Nominal voltage	70.0 V
Ignition voltage	2.5 kVp
Nominal current	1.9 A

Photometric Data

Nominal luminous flux	5400 lm
Color temperature	9200 K
Color rendering index Ra	60
Aperature window (max)	5x3.8 mm
Working distance	37.7 mm

Physical Attributes & Dimensions





Electrode gap (cold)	1.0 mm
Lamp base	-
Diameter	46.0 mm
Length	max. 44 mm
Product weight	60.00 g

Product datasheet

Operating Conditions

Burning position	Any
Cooling	Forced

Lifetime Data

	(000)
Nominal lifetime	6000 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier 4052899258969 4052899224056			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	No declarable substances contained		

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899258969	SIRIUS HRI 140 W RO	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm ³	108.00 g
4052899258976	SIRIUS HRI 140 W RO	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	262.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.