Product datasheet



64317 C 45-15

6.6 A Current Controlled Halogen - Pk30d Base Lamps for Series Operation | High quality single end lamps with specially designed Pk30d base for optimal thermal performance

Areas of application

- Airfield Lighting



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistence to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



February 12, 2025, 03:07:51 64317 C 45-15

Technical data

General Product Information

Product number (Americas)	58910		
Product name (Americas)	6.6A 64317C 45-15 PK30D 100/CS 1/SKU		
LIF code	J1/76		
Global order reference	64317 C 45-15		

Electrical Data


Nominal wattage	45 W
Nominal voltage	6.8 V
Nominal current	6.6 A

Photometric Data

Nominal luminous flux	800 lm
Color temperature	3000 К
Light center length (LCL)	16.0 mm
Light center length (LCL) - (in)	0.63 in

Physical Attributes & Dimensions







Connector C, male flat

Lamp base	PK30d	
Diameter (in)	0.531 in	
Diameter	13.5 mm	
Length	56.0 mm	
Length with base excl. base pins/connection	36.00 mm	
Connector: presence	Yes	
Product weight	14.50 g	

Operating Conditions

Product datasheet

Burning position	s90			
Lifetime Data				
Nominal lifetime 1500 hr				
Environmental & Regulatory Information	on			
Information according Art. 33 of EU R	egulation (EC) 1907/2006 (REACh)			
Information according Art. 33 of EU R Primary article identifier	egulation (EC) 1907/2006 (REACh) 4008321345493			
Information according Art. 33 of EU R	egulation (EC) 1907/2006 (REACh)			
Information according Art. 33 of EU R Primary article identifier	egulation (EC) 1907/2006 (REACh) 4008321345493			
Information according Art. 33 of EU R Primary article identifier Declaration no. in SCIP database	egulation (EC) 1907/2006 (REACh) 4008321345493 d9e66819-e040-4c44-bee8-4fcca5312c8c			

Country specific information

Product code	METEL-Code	SEG number	STK number	UK Org
4008321345493	-	8327800	4739728	-
4008321345493	-	-	4739728	-

sufficient to allow safe use of the article.

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321345493	64317 C 45-15	Folding carton box 1	32 mm x 36 mm x 69 mm	0.09 dm ³	23.00 g
4008321345509	64317 C 45-15	Shipping carton box 100	341 mm x 191 mm x 154 mm	10.03 dm³	2341.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.