

HBO 200 W/DC TM

 $HBO \leq 200W$ Double End | Short arc lamps with an intense point source that provides a broad spectrum through the visible and ultraviolet ranges



Areas of application

- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Microscopy
- Solar Simulation

Product features and benefits

- High luminance / radiance with intense point source
- Broad spectral distribution in the visible and ultraviolet range
- Enhanced UV characteristics available on some types
- High arc stability





Technical data

General Product Information

| Product number (Americas) | 69163 | |
|---------------------------|-----------------------------|--|
| Product name (Americas) | HBO 200 W/DC TM 10/CS 1/SKU | |
| Family brand | НВО | |
| Lamp type | DOUBLE ENDED | |
| Global order reference | HBO 200 W/DC TM | |

Electrical Data

| Nominal wattage | 200 W |
|-----------------|----------------------|
| Nominal voltage | 57 V |
| Lamp voltage | 5765 V ¹⁾ |
| Lamp current | 3.04.3 A |
| Type of current | DC |


¹⁾ Initial electrical values

Photometric Data

| Nominal luminous flux | 9500 lm |
|---------------------------|-----------------------|
| Luminous intensity | 1000 cd ¹⁾ |
| Luminous efficacy | 50 lm/W |
| Light center length (LCL) | 40.0 mm |

 $^{^{1)}}$ Typical initial photometric value

Physical Attributes & Dimensions



| Base (anode) | SFc10-4 ¹⁾ |
|----------------|-----------------------|
| Base (cathode) | SFc10-4 ¹⁾ |
| Diameter (in) | 39.331 in |
| Diameter | 17.0 mm |

Product datasheet

| Length | 125.0 mm | |
|---|-------------------------|--|
| Length with base excl. base pins/connection | 102.00 mm ²⁾ | |
| Product weight | 33.00 g | |

¹⁾ With 8-32 UNC-3 B thread

Operating Conditions

| Burning position | s90 ¹⁾ |
|------------------|-------------------|
|------------------|-------------------|

¹⁾ Anode underneath

Lifetime Data

Environmental & Regulatory Information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | |
|---|--|--|--|
| Primary article identifier | 4008321137623 | | |
| Declaration no. in SCIP database | 5280e35b-70e6-48e0-ac95-d834d6ba11af | | |
| Candidate list substance 1 | Lead | | |
| CAS No. of substance 1 | 7439-92-1 | | |
| Safe use instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. | | |

²⁾ Maximum

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4008321137623 | HBO 200 W/DC TM | Folding carton box 1 | 82 mm x 42 mm x 191 mm | 0.66 dm ³ | 171.00 g |
| 4008321137630 | HBO 200 W/DC TM | Shipping carton box 10 | 305 mm x 235 mm x 200 mm | 14.38 dm³ | 2100.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.