# **OSRAM**

# Cube MX85-WD

Full-force LED meets long-lasting quality





**2 LED light functions**Work light and stylish X shape light



**Lighting distance up to 55 meters**Improved near field illumination



Beam angle 43.5° Exceptionally wide beam angle



#### Powerful LED working lights for off-road use

People who regularly drive in difficult terrain know the benefits of a strong and reliable LED high-beam headlight. Near field illumination is an ideal choice for off-road use. With an illuminance of one lux, the LED working light reaches a light distance of up to 55 meters. The beam angle of the lamp is 43.5 degrees. The working headlight for cars gives drivers two possible LED light functions. One is the classic working light and the other is the LED working spotlight that provides stylish X shape light. And the spotlight is compelling beyond its function as a LED working light. The LED headlights work to underscore the off-road style of the vehicle, clearly emphasizing and enhancing it once again. Compact, robust and durableParticularly when driving in off-road conditions, durability and quality are much sought-after attributes. The LEDriving Cube MX85-WD working lights have a robust polycarbonate lens and can stand up to the most difficult demands of off-road applications. Over and under voltage protection up to 18 volts automatically breaks the circuit when power exceeds the predetermined current for a specified amount of time. To maintain their durability, the powerful searchlights are additionally equipped with an integrated driver and thermal management system. This eliminates the risk of overheating during continuous use. Excellent compatibilityThe LEDriving Cube MX85-WD working lights have a diverse range of applications. They are suitable for use in everything from 4x4 cars to off-road, utility and industrial vehicles through to recreational or agricultural vehicles. It is important to note, however, that these powerful working lights for automobiles are permitted only for off-road applications and must not be used on public roads.

### Technical data

## **Product information**

Order reference	LEDDL101-WD
Application (Category and Product specific)	Working light application


### **Electrical data**

Nominal voltage	12.0 V
Nominal wattage	20 W

## Photometrical data

Luminous flux	1250 lm
Color temperature	6000 K
Light distance at 1lx	55 m

## Dimensions & weight



Product weight	500.00 g
Length	85.0 mm
Width	57.0 mm
Height	121.0 mm

## Lifespan

Lifespan Tc	5000 h
Guarantee	5 years

## Additional product data

Connector to lamp	Wire Kit
-------------------	----------

## **Capabilities**

Technology	LED
	220

## Certificates & standards

Standards	ECE R10
Approval marks – approval	E6 approval
Type of protection	IP67

## **Country specific categorizations**

	LEDDI 404 MID
Order reference	LEDDL101-WD

## Logistical data

Commodity code	851220009000

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899595279	Cube MX85-WD LEDDL101-WD	Folding carton box 1	133 mm x 118 mm x 103 mm	1.62 dm <sup>3</sup>	584.00 g
4052899595286	Cube MX85-WD LEDDL101-WD	Shipping carton box	282 mm x 252 mm x 242 mm	17.20 dm <sup>3</sup>	5073.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

	File
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application LEDriving D&W Image Video Bringing light to life (EN)
D	Movie application LEDriving Driving & Working Lights Reference Video (EN)
D	Movie application OSRAM LEDriving driving and working lights FX1000-CB SM (EN)
D	Movie application LEDriving driving & working lights in application (EN)
D	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)

## Legal advice

Permitted only for off-road use and not suitable for use on public roads

Precise terms and conditions at: www.osram.com/guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.













