
OSRAM

LEDinspect FLEXIBLE HEAD TORCH





Flexible Head Band

Soft padding and additional adjustable strap for optimal wearing comfort



Up to 115 Lumen

Three light functions: Up to 115 lm (high, up to 50 lm (low) and a red flashing function at the rear



Approx. 1.5 hours charging

With a charging time of only approx. 1.5 hours, this OSRAM lamp is quickly ready for use again



2-year OSRAM Guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Light is versatile

This high-quality flexible head torch from OSRAM is perfect for professional and private use. With three light functions high up to 115lm, low up to 50lm and a red flashing function at the rear, this head torch offers different setting options for a variety of tasks. The illumination integrated directly into the individual adjustable headband enables a wide and even distribution of light and can provide better illumination of the working area. The rechargeable battery allows up to 4.5h of operation at high power or up to 5.5h at low power and with a charging time of only approx. 1.5 hours, this OSRAM lamp is also quickly ready for use again. An USB Micro B charging cable to recharge the lithium battery is included in the scope of supply. In accordance with IP 42 protection rating, this head torch has protection against ingress of dust particles and against splashing water. The LEDinspect Flexible Head Torch has soft pads inside and additionally an adjustable strap for optimal wearing comfort. With a weight of only 62g and the flexible, foldable design, the product is easy to store and transport, making it ideal as a light for craft work, car repairs and everyday use. OSRAM also provides a 2-year guarantee**For precise conditions please refer to: www.osram.com/am-guarantee

Technical data

Product information

Application (Category and Product specific)	LED inspection lights
---	-----------------------

General Product Information

Global order reference	LEDIL414
------------------------	----------

Electrical Data

Nominal wattage	3 W
Nominal voltage	3.7 V

Photometric Data

Color temperature	6000 K
Nominal luminous flux	115 lm
Light color LED	White

Physical Attributes & Dimensions

Product weight	62.00 g
Length	245.0 mm
Width	25.0 mm
Height	25.0 mm

LED module information

Number of LEDs per module 1	
-----------------------------	--

Colors & materials

Base color	Black / Orange

Lifetime Data

Guarantee	2 years
Guarantee	2 years

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Battery	High-quality lithium-ion battery 3.7V Li-po 1000mAh

Capabilities

Certificates & standards

Standards	CE / EMC / MSDS / ROHS / UKCA

Logistical data

Watt hour per battery 3.70

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of declaration	26-06-2024			
Candidate list substance 1	Lead			
CAS No. of substance 1	7439-92-1			
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.			
Declaration no. in SCIP database	3ee5100c-84cd-4784-ba6a-aabf9f12ebcb			

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899631014	INSPECTION LAMP		- x - x -	5.82 dm³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.* for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

