

## 64331 SP-A 30-10

6.6 A Current Controlled Halogen - Reflector Lamps for Series Operation | 6.6 A reflector lamps for airfield lighting that provide accurate filament alignment for precision optics


### Areas of application

- Airfield Lighting



### Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



Technical data

General Product Information

|                           |                                     |
|---------------------------|-------------------------------------|
| Product number (Americas) | 58506                               |
| Product name (Americas)   | 6.6A 30W MR16 64331A SP 20/CS 1/SKU |
| Global order reference    | 64331 SP-A 30-10                    |

Electrical Data

|                 |       |
|-----------------|-------|
| Nominal wattage | 30 W  |
| Nominal current | 6.6 A |
| Type of current | AC    |

Photometric Data

|                          |          |
|--------------------------|----------|
| Axial luminous intensity | 18000 cd |
| Color rendering index Ra | 100      |

Physical Attributes & Dimensions



Connector A, female

|                       |                                |
|-----------------------|--------------------------------|
| Lamp base             | Leads w/female flat connectors |
| Diameter              | 50.4 mm                        |
| Diameter (in)         | 1.984 in                       |
| Diameter              | 50.4 mm                        |
| Length                | 48.0 mm                        |
| Connector: presence   | Yes                            |
| Connection with cable | Yes                            |
| Mains terminals       | Leads w/female flat connectors |
| Product weight        | 23.00 g                        |

Lifetime Data

|                  |         |
|------------------|---------|
| Nominal lifetime | 1000 hr |
|------------------|---------|

Environmental & Regulatory Information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                    |
|---|------------------------------------|
| Primary article identifier  | 4008321102560                      |
| Declaration no. in SCIP database                                      | No declarable substances contained |
| Candidate list substance 1  | No declarable substances contained |

# Product datasheet

## Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

## Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|---|----------------------|--------------|
| 4008321102560 | 64331 SP-A 30-10    | Folding carton box<br>1         | 48 mm x 48 mm x<br>59 mm                | 0.14 dm <sup>3</sup> | 36.00 g      |
| 4008321102577 | 64331 SP-A 30-10    | Shipping carton box<br>20       | 257 mm x 109 mm x<br>131 mm             | 3.71 dm <sup>3</sup> | 816.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.