

64337 A 45-15

6.6 A Current Controlled Halogen - Reflector Lamps for Series Operation | 6.6 A reflector lamps for airfield lgihting that provide accurate filament alignment for precision optics

Areas of application

- Airfield Lighting



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistence to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free





Technical data

General Product Information

Product number (Americas)	58907		
Product name (Americas)	6.6A 45W MR16 64337A 45-15 20/CS 1/SKU		
Lamp type	SINGLE ENDED		
Global order reference	64337 A 45-15		


Electrical Data


Nominal wattage	45 W	
Nominal current	6.6 A	
Type of current	AC	

Photometric Data

Nominal luminous flux	19000 lm	
Axial luminous intensity	21000 cd	
Color temperature	3200 K	
Color rendering index Ra	100	

Physical Attributes & Dimensions





Connector A, female

Lamp base	Leads w/female flat connectors
Diameter	50.4 mm
Diameter (in)	1.984 in
Diameter	50.4 mm
Length	45.0 mm
Length with base excl. base pins/connection	45.00 mm
Connector: presence	Yes
Connection with cable	Yes
Mains terminals	Leads w/female flat connectors

Product datasheet

Operating Conditions

Lifetime Data

Nominal lifetime	1500 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Primary article identifier 4008321102515			
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1 No declarable substances contained			

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321102515	OSRH64337A	-	-	-
4008321102515	OSRH64337A	-	-	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321102515	64337 A 45-15	Folding carton box 1	50 mm x 50 mm x 62 mm	0.16 dm ³	38.00 g
4008321102720	64337 A 45-15	Shipping carton box 20	257 mm x 110 mm x 131 mm	3.70 dm ³	908.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.