

64615 HLX

Halogen (< 75 V) with Reflector | OSRAM reflector low voltage halogen lamps provide precision optical alignment for medical and industrial fiber optic illuminators, microscopy, and surgical overhead lighting




Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable



Technical data

General Product Information

Global order reference	64615 HLX
Product number (Americas)	54126
Product name (Americas)	64615 HLX EFN 75W 12V 20/CS 1/SKU
Family brand	XENOPHOT (HLX)
ANSI code	EFN
LIF code	A1/230


Electrical Data

Nominal wattage	75 W
Nominal voltage	12.0 V
Type of current	AC

Photometric Data

Focal length	32.0 mm
--------------	---------

Physical Attributes & Dimensions



Lamp base	GZ6.35
Diameter	51.0 mm
Diameter (in)	2.008 in
Diameter	51.0 mm
Length	42.0 mm
Coating	Dichroic
Product weight	28.00 g

Operating Conditions

Burning position	p90/p15
------------------	---------

Product datasheet

Cooling	Forced
Minimum diameter of lamp enclosure	51.0 mm

Lifetime Data

Nominal lifetime	50 hr
------------------	-------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300006796
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300006796	OSRH64615HLX	-	-	-
4050300006796	OSRH64615HLX	-	-	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300006796	64615 HLX	Folding carton box 1	46 mm x 46 mm x 58 mm	0.12 dm ³	36.00 g
4050300665528	64615 HLX	Shipping carton box 20	238 mm x 105 mm x 123 mm	3.07 dm ³	778.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.