


64626 HLX

Halogen (< 75 V) Single End | OSRAM single end low voltage halogen lamps provide high quality light to meet the high demands of the medical and scientific markets



Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable



Technical data

General Product Information

Product number (Americas)	54038
Product name (Americas)	EHE 64626 HLX 100W 12V 30/CS 1/SKU
Family brand	XENOPHOT (HLX)
ANSI code	EHE
LIF code	A1/45
Product remark	Available on request
Global order reference	64626 HLX


Electrical Data

Nominal wattage	100 W
Nominal voltage	12.0 V
Type of current	AC

Photometric Data

Nominal luminous flux	3500 lm
Illuminated field	4.2*2.3 mm ²
Color temperature	3450 K
Color rendering index Ra	100
Light center length (LCL)	18.0 mm
Light center length (LCL) - (in)	0.702 in

Physical Attributes & Dimensions



Lamp base	PG22
Diameter	11.5 mm
Diameter (in)	0.472 in
Diameter	11.5 mm

Product datasheet

Length	48.0 mm
Product weight	8.00 g

Operating Conditions

Burning position	s90
------------------	-----

Lifetime Data

Nominal lifetime	50 hr
------------------	-------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300006765
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300006765	OSRH64626HLX	-	-	-
4050300006765	OSRH64626HLX	-	-	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300006765	64626 HLX	Folding carton box 1	24 mm x 23 mm x 70 mm	0.03 dm ³	11.00 g
4050300236421	64626 HLX	Shipping carton box 30	158 mm x 131 mm x 81 mm	1.68 dm ³	372.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.