### Product datasheet



# 64647 120 W 24 V

Halogen (< 75 V) Single End | OSRAM single end low voltage halogen lamps provide high quality light to meet the high demands of the medical and scientific markets


#### Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead



#### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable



#### Technical data

### **General Product Information**

Product number (Americas)	54320	
Product name (Americas) 64647 120W 24V 40/CS 1/SKU		
Lamp type	SINGLE END	
ANSI code	-	
LIF code	-	
Global order reference	64647	


### **Electrical Data**

Nominal wattage	113 W
Nominal voltage	22.8 V
Type of current	AC

### **Photometric Data**

Nominal luminous flux	3600 lm	
Illuminated field	2.3*6.4 mm <sup>2</sup>	
Color rendering index Ra	100	
Light center length (LCL)	30.0 mm	
Light center length (LCL) - (in)	1.18 in	

# **Physical Attributes & Dimensions**



Lamp base	G6.35
Diameter	13.0 mm
Diameter	13.0 mm
Length	44.0 mm
Product weight	3.00 g

# Product datasheet

# **Operating Conditions**

Burning position	Any

#### Lifetime Data

Nominal lifetime

1000 hr

# Environmental & Regulatory Information

# Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Primary article identifier	4008321107114		
Declaration no. in SCIP database No declarable substances contained			
Candidate list substance 1	No declarable substances contained		

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321107114	OSRH64647	-	-	-
4008321107114	OSRH64647	-	-	-

# Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321107114	64647 120 W 24 V	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm³	5.00 g
4008321107121	64647 120 W 24 V	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm³	241.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.