

64655 HLX

Halogen (< 75 V) Single End | OSRAM single end low voltage halogen lamps provide high quality light to meet the high demands of the medical and scientific markets





Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable



Technical data

General Product Information

Product number (Americas)	54254
Product name (Americas)	EHJ 64655 HLX 250W 40/CS 1/SKU
Family brand	XENOPHOT (HLX)
Lamp type	SE
ANSI code	EHJ
LIF code	A1/223
Global order reference	64655 HLX

Electrical Data

Nominal wattage	250 W
Nominal voltage	24.0 V
Type of current	AC

Photometric Data

Nominal luminous flux	10000 lm
Illuminated field	7.1*3.6 mm ²
Color temperature	3550 K
Color rendering index Ra	100
Light center length (LCL)	33.0 mm
Light center length (LCL) - (in)	1.287 in

Physical Attributes & Dimensions

Lamp base	G6.35
Diameter	12.5 mm
Diameter (in)	0.551 in
Diameter	12.5 mm
Length	55.0 mm
Product weight	4.08 g

Operating Conditions

Burning position	s90
------------------	-----

Lifetime Data

Nominal lifetime	50 hr
------------------	-------

Environmental & Regulatory Information

Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300006734
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300006734	OSRH64655HLX40	8327822	4739432	-
4050300006734	OSRH64655HLX40	-	4739432	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300006734	64655 HLX	Folding carton box 1	25 mm x 22 mm x 70 mm	0.04 dm ³	7.00 g
4050300890807	64655 HLX	Shipping carton box 40	150 mm x 113 mm x 118 mm	2.00 dm ³	353.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.