

64653 HLX

Halogen (< 75 V) with Reflector | OSRAM reflector low voltage halogen lamps provide precision optical alignment for medical and industrial fiber optic illuminators, microscropy, and surgical overhead lighting



Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable





Product datasheet

Technical data

General Product Information

Global order reference	64653 HLX		
Product number (Americas)	54212		
Product name (Americas)	ELC 64653 HLX 250W 24V 20/CS 1/SKU		
ANSI code	ELC		
LIF code	A1/259		


Electrical Data

Nominal wattage	250 W
Nominal voltage	24.0 V
Type of current	AC

Photometric Data

Nominal luminous flux	900 lm
Color temperature	3400 K
Color rendering index Ra	100
Focal length	35.0 mm

Physical Attributes & Dimensions



Lamp base	GX5.3
Diameter	51.0 mm
Diameter (in)	2.008 in
Diameter	51.0 mm
Length	44.5 mm
Coating	True
Product weight	28.70 g

Product datasheet

Operating Conditions

Burning position	Any	
Cooling	Forced	
Minimum diameter of lamp enclosure	51.0 mm	

Lifetime Data

Nominal lifetime	50 hr
Nominal medine	30 III

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Primary article identifier	4052899329348	
Declaration no. in SCIP database	No declarable substances contained	
Candidate list substance 1	No declarable substances contained	

Country specific information

Product code	METEL-Code	SEG-No.	STK number	UK Org
4052899329348	-	-	4736553	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899329348	64653 HLX	Folding carton box 1	46 mm x 46 mm x 58 mm	0.12 dm ³	37.00 g
4052899329355	64653 HLX	Shipping carton box 20	238 mm x 105 mm x 123 mm	3.07 dm ³	792.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.