


## HPL 93729 LL 750 W 230 V

Halogen (> 130 V) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets



### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable to 0% with traditional amber shift



Technical data

General Product Information

Product number (Americas)	54670
Product name (Americas)	93729 HPL 750W230V/X 12/CS 1/SKU
Family brand	HPL
ANSI code	-
LIF code	-
Global order reference	HPL 93729 LL 750 W 230 V

Electrical Data


Nominal wattage	750 W
Nominal voltage	230 V
Type of current	AC

Photometric Data

Nominal luminous flux	15600 lm
Useful luminous flux ( $\Phi_{use}$ )	15595 lm
$\Phi_{use}$ value refers to luminous flux	360
Illuminated field	15.5*11.0 mm <sup>2</sup> <sup>1)</sup>
Color temperature	3050 K
Correlated color temperature CCT	3038 K
Chromaticity coordinate x	0.434
Chromaticity coordinate y	0.403
Color rendering index Ra	100
Light center length (LCL)	60.3 mm
Light center length (LCL) - (in)	2.352 in

<sup>1)</sup> Type of filament 6-C8

Physical Attributes & Dimensions



Lamp base	G9.5 w/Hsink
Diameter	19.0 mm
Diameter (in)	0.748 in
Diameter	19.0 mm
Length	104.0 mm
Filament	6-C8
Product weight	57.00 g

Operating Conditions

Burning position	Any
Dimmable	Yes

Lifetime Data

Nominal lifetime	1500 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321090324
Energy efficiency class	G
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321090324	OSRHPL93729LL	-	-	-

# Product datasheet

## Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321090324	HPL 93729 LL 750 W 230 V	Folding carton box 1	40 mm x 40 mm x 128 mm	0.21 dm <sup>3</sup>	80.00 g
4052899246881	HPL 93729 LL 750 W 230 V	Shipping carton box 12	177 mm x 136 mm x 152 mm	3.70 dm <sup>3</sup>	1160.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.