

GUELL 2.5 A/W




Part number	306126
Lampholder:	LED
Light Source:	LED
Wattage:	158 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	21619 lm
Luminaire lumen output:	17511 lm
L:	L70
B:	B10
Lifetime:	130000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	40°




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminum housing chemically pre-treated and painted with polyester powder coating
 - Flat tempered glass diffuser
 - Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Asymmetrical optic
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket


PHOTOMETRIC DATA




TECHNICAL DRAWINGS



GUELL 2.5



310963
Cover GUELL 2.5
Metallic grey



310965
Protective grid GUELL 2.5



310982
Wall mount support 1000 mm
Metallic grey



310967
Double pole top support GUELL 2.5
Metallic grey



310966
Single pole top support GUELL 2.5
Metallic grey