
PERFORMANCE IN LIGHTING



ART.: 8333291266310

FL ROUND 333 PL OP





Art.: 8333291266310, FL ROUND 333 PL, Direct, 26W, 3000K, Driver dali, Symmetrical, > 75°, White, Suspended round LED luminaire for indoors, consisting of: Housing made from sheet steel and diecast aluminium, powder-coated / The fitting is available with different light optics: Micro-prismatic diffuser for efficient light diffusion, glare reduction and a high uniformity / Opal white diffuser cover for optimum light diffusion and excellent uniformity / LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the cover / Light distribution direct or predominantly direct / Glare prevention in accordance with DIN EN 12464-1 (for designs with micro prism) / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam ≤ 3 SDCM / Dimmable via TouchDIM / Complete with steel suspension cable (1.5 m), transparent power cord and ceiling rose / Complete with electric converter

Connected load 26 W **Luminous flux** 3040 lm **Efficiency** 117 lm/W 3000K Colour temperature Colour rendering (CRI) 80 **IP class** 20 220 - 240 V **Nominal voltage** Colour WH-RAL9016 **UGR** ≤ 28

90° 90°
60° 60°
45° 45°
30° 15° 15° 30°
400 cd/klm