


ART.: 8555491513410

FL ROUND 555 PL OP CORONA



Art.: 8555491513410, FL ROUND 555 PL, Direct/indirect, 50W, 4000K, Driver static, Symmetrical, > 75°, White, Suspended round LED luminaire for indoors, consisting of: Housing made from sheet steel and diecast aluminium, powder-coated / The fitting is available with different light optics: Micro-prismatic diffuser for efficient light diffusion, glare reduction and a high uniformity / Opal white diffuser cover for optimum light diffusion and excellent uniformity / LED Sidelight-Technology and light orienting plastic optic for a homogenous light distribution over the entire area of the cover / Light distribution direct or predominantly direct / Glare prevention in accordance with DIN EN 12464-1 (for designs with micro prism) / Colour rendering index $R_a > 80$ / Colour tolerance according to MacAdam ≤ 3 SDCM / Dimmable via TouchDIM / Complete with steel suspension cable (1.5 m), transparent power cord and ceiling rose / Complete with electric converter

Connected load	50 W
Luminous flux	6390 lm
Efficiency	128 lm/W
Colour temperature	4000K
Colour rendering (CRI)	80
IP class	20
Nominal voltage	220 – 240 V
Colour	WH-RAL9016
UGR	≤ 25

