




ART.: 8720761105930 SL720SL XL LED MICROPRISMA





Art.: 8720761105930, SL720SL XL LED, Micro-prism, 118W, 2700K - 6200K (TW), Driver dali, 1035mm, Symmetrical - Direct / indirect, Grey, LED free-standing luminaire for interior, including: Steel sheet head, extruded aluminium profile post, steel sheet base, powder painted / Angle of the lamp head adjustable using a set screw / Microprismatic diffuser for efficient light diffusion, glare reduction and a high uniformity / Direct / indirect light distribution / Suitable for simultaneous lighting of 2 workstations / Colour rendering index Ra > 80 / Colour tolerance according to MacAdam = 3 SDCM / Direct share of light dimmable; colour temperature 4000K / Complete with flexible power cord with plug / DALI dimmable / VDU application suitable acc. to EN 12464-1 / Light colour and brightness of indirect light share manually adjustable via Tunable White control / 3000 K colour temperature version on demand / Special colour versions available upon request

Connected load 118 W
Luminous flux 14300 lm
Efficiency 121 lm/W

Colour temperature 2700K - 6200K (TW)

Colour rendering (CRI) 80 IP class 20

Nominal voltage 220 – 240 V Colour GR-RAL9006

UGR 5,0 Glare control √

