


ART.: 8720761775910

SL720SL L LED MICROPRISMA



Art.: 8720761775910, SL720SL L LED, Micro-prism, 85W, 2700K - 6200K (TW), Driver dali, 705mm, Direct / indirect, White, LED free-standing luminaire for interior, including: Steel sheet head, extruded aluminium profile post, steel sheet base, powder painted, Micro-prismatic diffuser for efficient light diffusion, glare reduction and a high uniformity, Direct / indirect light distribution, Colour rendering index Ra > 80, Colour tolerance according to MacAdam ≤ 3 SDCM Direct share of light dimmable; colour temperature 4000K, Complete with flexible power cord with plug, VDU application suitable acc. to EN 12464-1, Sensor device available with task oriented PIRdetector and daylight control, Light colour and brightness of indirect light share manually adjustable via Tunable White control, Light colour and brightness of indirect light share automatically adjustable via HCL (Human Centric Lighting) for wholesome and performance-enhancing management of the biorhythm, 3000 K colour temperature version on demand, Special colour versions available upon request

Connected load	85 W
Luminous flux	10120 lm
Efficiency	119 lm/W
Colour temperature	2700K - 6200K (TW)
Colour rendering (CRI)	80
IP class	20
Nominal voltage	220 – 240 V
Colour	RAL 9016
UGR	6,2
Glare control	✓

