

ACCESSOIRES ACIER GALVANISÉ A JOINT

Réductions coniques - REDV




Description

- Réduction conique à joint
- Etanchéité Classe C

Dimensions

- REDV $\varnothing A - \varnothing B$
- Mâle / Mâle



| Référence | Code | $\varnothing A$ (mm) | $\varnothing B$ (mm) |
|--------------|---------|----------------------|----------------------|
| REDV 100/80 | 865 698 | 100 | 80 |
| REDV 125/80 | 865 699 | 125 | 80 |
| REDV 125/100 | 866 313 | 125 | 100 |
| REDV 160/80 | 866 343 | 160 | 80 |
| REDV 160/100 | 866 344 | 160 | 100 |
| REDV 160/125 | 867 835 | 160 | 125 |
| REDV 200/100 | 866 345 | 200 | 100 |
| REDV 200/125 | 865 686 | 200 | 125 |
| REDV 200/160 | 865 687 | 200 | 160 |
| REDV 250/125 | 865 697 | 250 | 125 |
| REDV 250/160 | 865 688 | 250 | 160 |
| REDV 250/200 | 865 689 | 250 | 200 |
| REDV 315/160 | 865 690 | 315 | 160 |
| REDV 315/200 | 865 691 | 315 | 200 |
| REDV 315/250 | 866 463 | 315 | 250 |
| REDV 355/200 | 866 464 | 355 | 200 |
| REDV 355/250 | 866 465 | 355 | 250 |
| REDV 355/315 | 866 466 | 355 | 315 |
| REDV 400/200 | 865 693 | 400 | 200 |
| REDV 400/250 | 865 694 | 400 | 250 |
| REDV 400/315 | 865 695 | 400 | 315 |
| REDV 400/355 | 865 696 | 400 | 355 |
| REDV 450/250 | 866 467 | 450 | 250 |
| REDV 450/315 | 866 468 | 450 | 315 |
| REDV 450/355 | 866 469 | 450 | 355 |
| REDV 450/400 | 866 470 | 450 | 400 |
| REDV 500/250 | 866 471 | 500 | 250 |
| REDV 500/315 | 866 472 | 500 | 315 |
| REDV 500/355 | 866 473 | 500 | 355 |

| Référence | Code | $\varnothing A$ (mm) | $\varnothing B$ (mm) |
|--------------|---------|----------------------|----------------------|
| REDV 500/400 | 866 474 | 500 | 400 |
| REDV 500/450 | 866 475 | 500 | 450 |
| REDV 560/315 | 866 476 | 560 | 315 |
| REDV 560/355 | 866 477 | 560 | 355 |
| REDV 560/400 | 866 478 | 560 | 400 |
| REDV 560/450 | 866 479 | 560 | 450 |
| REDV 560/500 | 866 480 | 560 | 500 |
| REDV 630/355 | 866 481 | 630 | 355 |
| REDV 630/400 | 866 482 | 630 | 400 |
| REDV 630/450 | 866 483 | 630 | 450 |
| REDV 630/500 | 866 484 | 630 | 500 |
| REDV 630/560 | 866 485 | 630 | 560 |
| REDV 710/400 | 866 486 | 710 | 400 |
| REDV 710/450 | 866 487 | 710 | 450 |
| REDV 710/500 | 866 488 | 710 | 500 |
| REDV 710/560 | 866 489 | 710 | 560 |
| REDV 710/630 | 866 490 | 710 | 630 |

Bouchons à joint - BRTV




Description

- Bouchon raccord à joint
- Etanchéité Classe C
- Mâle

Dimensions

- BRTV \varnothing



| Référence | Code | \varnothing (mm) |
|-----------|---------|--------------------|
| BRTV 80 | 865 517 | 80 |
| BRTV 100 | 865 518 | 100 |
| BRTV 125 | 865 519 | 125 |
| BRTV 160 | 865 520 | 160 |
| BRTV 200 | 865 521 | 200 |
| BRTV 250 | 865 522 | 250 |
| BRTV 315 | 865 523 | 315 |

| Référence | Code | \varnothing (mm) |
|-----------|---------|--------------------|
| BRTV 355 | 865 524 | 355 |
| BRTV 400 | 865 525 | 400 |
| BRTV 450 | 865 526 | 450 |
| BRTV 500 | 865 527 | 500 |
| BRTV 560 | 865 528 | 560 |
| BRTV 630 | 865 529 | 630 |