

ACCESSOIRES ACIER GALVANISÉ A JOINT



Tés Equerres 90° - TEV




Description

- Té équerre à joint
- Etanchéité Classe C
- Orientation 90°

Dimensions

- TEV $\varnothing A - \varnothing B / 90^\circ$
- Mâle / Mâle / Mâle



Référence	Code	$\varnothing A$ (mm)	$\varnothing B$ (mm)
TEV 125/125/90°	867 774	125	125
TEV 160/125/90°	866 683	160	125
TEV 160/160/90°	867 775	160	160
TEV 200/125/90°	866 684	200	125
TEV 200/160/90°	867 776	200	160
TEV 200/200/90°	867 777	200	200
TEV 250/125/90°	866 685	250	125
TEV 250/160/90°	867 778	250	160
TEV 250/200/90°	867 779	250	200
TEV 250/250/90°	867 780	250	250
TEV 315/125/90°	866 686	315	125
TEV 315/160/90°	867 781	315	160
TEV 315/200/90°	867 782	315	200
TEV 315/250/90°	867 783	315	250
TEV 315/315/90°	867 784	315	315
TEV 355/125/90°	866 687	355	125
TEV 355/160/90°	867 785	355	160
TEV 355/200/90°	867 786	355	200
TEV 355/250/90°	867 787	355	250
TEV 355/315/90°	867 788	355	315
TEV 355/355/90°	867 789	355	355
TEV 400/125/90°	866 688	400	125
TEV 400/160/90°	867 790	400	160
TEV 400/200/90°	867 791	400	200
TEV 400/250/90°	867 792	400	250
TEV 400/315/90°	867 793	400	315
TEV 400/355/90°	867 794	400	355
TEV 400/400/90°	867 795	400	400
TEV 450/125/90°	866 689	450	125
TEV 450/160/90°	866 690	450	160
TEV 450/200/90°	866 691	450	200
TEV 450/250/90°	866 692	450	250
TEV 450/315/90°	866 693	450	315
TEV 450/355/90°	866 694	450	355
TEV 450/400/90°	866 695	450	400

Référence	Code	$\varnothing A$ (mm)	$\varnothing B$ (mm)
TEV 450/450/90°	866 696	450	450
TEV 500/125/90°	866 697	500	125
TEV 500/160/90°	866 698	500	160
TEV 500/200/90°	866 699	500	200
TEV 500/250/90°	866 700	500	250
TEV 500/315/90°	867 796	500	315
TEV 500/355/90°	867 797	500	355
TEV 500/400/90°	867 798	500	400
TEV 500/450/90°	866 701	500	450
TEV 500/500/90°	867 799	500	500
TEV 560/125/90°	866 702	560	125
TEV 560/160/90°	866 703	560	160
TEV 560/200/90°	866 704	560	200
TEV 560/250/90°	866 705	560	250
TEV 560/315/90°	866 706	560	315
TEV 560/355/90°	866 707	560	355
TEV 560/400/90°	866 708	560	400
TEV 560/450/90°	866 709	560	450
TEV 560/500/90°	866 710	560	500
TEV 560/560/90°	866 711	560	560
TEV 630/125/90°	866 712	630	125
TEV 630/160/90°	866 713	630	160
TEV 630/200/90°	866 714	630	200
TEV 630/250/90°	866 715	630	250
TEV 630/315/90°	866 716	630	315
TEV 630/355/90°	866 717	630	355
TEV 630/400/90°	866 718	630	400
TEV 630/450/90°	866 719	630	450
TEV 630/500/90°	866 720	630	500
TEV 630/560/90°	866 721	630	560
TEV 630/630/90°	866 722	630	630

Manchons Raccords - MRTV




Description

- Manchon raccord à joint
- Etanchéité Classe C

Dimensions

- MRTV \varnothing
- Mâle / Mâle



Référence	Code	\varnothing (mm)
MRTV 125	867 855	125
MRTV 160	867 856	160
MRTV 200	867 857	200
MRTV 250	867 858	250
MRTV 315	867 859	315
MRTV 355	867 860	355

Référence	Code	\varnothing (mm)
MRTV 400	867 861	400
MRTV 450	866 676	450
MRTV 500	867 862	500
MRTV 560	866 677	560
MRTV 630	866 678	630