

NSR SENSITIVE

Technical Data Sheet

Product name: NSR Sensitive

Creation date: 10/11/2017 Version: 1.2

Replaces: 1.1

1 : General description

Release agent for plastics and rubbers that need an ulterior finishing..

2 : Features

- Colourless
- Resists high temperatures
- Allows post moulding operations like painting, gluing, thermos welding.

3: Applications

Moulding of low density PE, sensible to stress cracking

4: Directions

- Do not mix with other release agents.
- Apply on a clean and dry surface.
- Shake the Aerosol during 1 min.
- Apply a uniform film.
- Re-apply whenever the demoulding gets difficult.

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5: Typical product data (without propellant)

Alkyl methyl oil in a solvent

- | | |
|-------------------------|--------------|
| • Aspect | : liquid |
| • Colour | : colourless |
| • Viscosity | : 3000 cPs |
| • Operating temperature | : max 150°C |



6: Packaging

Aerosol 12x500 ML

Bulk 2 x 5 Lt

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.