

SR THERMO

Technical Data Sheet

Product name: SR Thermo
Version: 2.0

Creation date: 09/12/19
Replaces: 1.0

Section 1 : General description

Silicone based release agent for polyester and epoxy moulding.

Section 2 : Features

- Colourless
- Operational till 200°C
- Good clinch on the surface support
- Suitable for all types of support
- Ameliorates the surface appearance of the moulded parts.

Section 3: Applications

Moulding of polyesters and epoxies at room temperature and elevated temperatures. Very efficient for small and medium sized surfaces.

Section 4: Directions

- In case other products have been used before, clean the surface to be treated.
- Apply a uniform film.
- Allow the solvents to evaporate.
- Re-apply as soon as the release shows to become more difficult.

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

Section 5: Typical product data (without propellant)

Aspect : liquid
Colour : colourless



Section 6: Packaging

Aerosol 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.