

Part number

CX 17 DF



Female modular insert, Mixo series, crimp connection, 17 poles, 1 module, 10 A 160 V 2,5 kV 3

Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate
Series	Mixo	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHs conformity	Compliant
Gender	Female	China RoHs - EFUP	E
N. of poles	17 poles	REACH SVHC substances	No
Size	1 module	Approvals / Standards	
Specification	Standard & HNM (High Number of Matings)	Reference standard	EN 61984:2009-06
Technical data		Certifications	CSAc, CQC, DNV, BV, EAC
Current	10 A	UL	ECBT2
Voltage	160 V	cUL	ECBT8
Rated impulse withstand voltage	2,5 kV	General ordering information	
Pollution degree	3	EAN13 code	8015747109765
Rated voltage according to UL/CSA	250 V	eCl@ss 8.1	27440205
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	ETIM 7.0	EC000438
Further technical details		Packaging Information	
Characteristics according to EN 61984	10A 160V 2.5kV 3; 10A 250V 4kV 2	Packaging length	180,00 mm
Insulation resistance	≥ 10 GΩ	Packaging height	120,00 mm
Contact resistance	≤ 3 mΩ	Packaging width	155,00 mm
Weight	10,00 g	Packaging weight	0,79 kg
Operating temperature range (min, max)	-40 °C ... +125 °C	Packaging volume	3,35 dm ³
UL 94 flammability rating	V-0	Packaging description	Carton box
		Packaging quantity	60 Pcs
		Packaging EAN code	8015747221337
		Sub-packaging length	35,00 mm
		Sub-packaging height	40,00 mm
		Sub-packaging width	155,00 mm
		Sub-packaging weight	0,13 kg
		Sub-packaging volume	0,22 dm ³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747173278

Part number



CX 17 DF





Catalogue drawings

Catalogue drawings


CX 17 DF, CX 17 DM




M



F




F



M

MIXO series (CX 17)



Notes

STANDARD & HNM (High Number of Matings) MODULES

Standard:

-when in combination with standard contacts and standard frames (CX ... TF/TM), must be mounted either in traditional enclosures or in COB panel supports (both up to 500 matings).

HNM (High Number of Matings):

-when in combination with HNM contacts and HNM frames (RX ... TF/RM), must be mounted either in HNM enclosures (up to 10.000 matings) or in traditional enclosures with one lever (up to 5.000 matings).

Dimensions shown in mm are not binding and may be changed

without notice.
