

Product Environmental Profile

UPS
KEOR Compact 10kVA



LEGRAND'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites**

Of all Legrand sites worldwide, over 85% are ISO 14001-certified [sites belonging to the Group for more than five years].

- Offer our customers environmentally friendly solutions**

Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.

- Involve the environment in product design and provide informations in compliance with ISO 14025**

Reduce the environmental impact of products over their whole life cycle.

Provide our customers with all relevant information (composition, consumption, end of life, etc.).



REFERENCE PRODUCT

Function	To protect the load of 10 kW against input power failure during 10 years and switch to the energy storage system to avoid power outage.
Reference Product	
	LG-311100
	Parallelable triphase UPS with Bypass Keor Compact 10 kVA - 9 kW - Performance classification: VFI-SS-111 Cabinet 260 x 850 x 890 mm. Mass (without packaging) = 74 kg. Location of the principal manufacturing plants : China. Power factor >0.99. Input Dependency Characteristics according to IEC 62040-3 : VFI multimode. Redundancy : N+1.

The company reserves the right to change specifications and designs without notice. All illustrations, descriptions, dimensions and weights in the document are for guidance and cannot be held binding on the company.



PRODUCTS CONCERNED

The environmental data is representative of the following products:

LG-311100

Product Environmental Profile

UPS
KEOR Compact 10kVA



■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU and its delegated directive 2015/863/EU.

Total weight of Reference Product	89,4 Kg (all packaging included)				
Plastics as % of weight		Metals as % of weight		Others as % of weight	
Polyamide	1,3 %	Steel	56,8 %	Electronic cardboards	14,4 %
PMMA	0,7 %	Aluminum	3,9 %	Cables / electric wires	1,3 %
Thermoset	0,3 %	Copper alloys	3,0 %		
PBT	0,3 %				
SBR rubber	0,3 %				
PET	0,2 %				
Other plastics	0,1 %				
Packaging					
Polystyrene	0,2 %			Wood	10,8 %
Polyethylene (LDPE)	0,1 %			Paper / cardboard	6,3 %
Total plastics	3,5 %	Total metals	63,7 %	Total others	32,8 %

Estimated recycled material content: 30 % by mass.



■ MANUFACTURE

This Reference Product comes from a site that has received ISO14001 certification.



■ DISTRIBUTION

Products are distributed from logistics centres located with a view to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 1000 km by road plus 19000 km by sea from our warehouse to the local point of distribution into the worldwide market. Packaging is compliant with applicable regulation concerning packaging and packaging waste. At their end of life, its recyclability rate is 95 % (in % of packaging weight).



■ INSTALLATION

For the installation of the product, only standard tools are needed.



■ USE

Under normal conditions of use, this product requires maintenance. In particular these are the components considered to be substituted during 10 years:

- DC and AC capacitors of filtering and related PCB (1 time);
- Fans (2 times);
- Power supply PCB (1 time).

Product Environmental Profile

UPS
KEOR Compact 10kVA



END OF LIFE

The product end-of-life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse. This product falls within the scope of the WEEE directive (2012/19/EU). Therefore it must be processed through local WEEE recycling/recovery channels.

• Elements to process specifically:

In accordance with the requirements of this Directive, the following components must be removed and sent to specific channels for processing which comply with the WEEE Directive 2012/19/EU:

- electronic cards more than 10 cm² : 12700 g

• Extended producer responsibility:

The sale of this product is subject to a contribution to eco-organisations in each country responsible for managing end-of-life products in the field of application of the European Waste Electronic and Electrical Equipment Directive.

• Recyclability rate:

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 91 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 2 %
- metal materials (excluding packaging) : 64 %
- other materials (excluding packaging) : 9 %
- packaging (all types of materials) : 16 %



ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end-of-life. It is representative from products marketed and used all around the world, in compliance with the local current standards.

For each phase, the following modelling elements were taken in account:

Manufacture	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
Distribution	Transport between the last Group distribution centre and an average delivery point in the sales area.
Installation	The end of life of the packaging.
Use	<ul style="list-style-type: none"> • Product category: «PSR-0010-ed1.1-EN-2015 10 16 - UPS» • Use scenario: consumption of 49932 kW during the 10 years working life due to an average energy efficiency of 92,4 %. The substitution of the maintenance components as indicated in the Use paragraph. This modelling duration does not constitute a minimum durability requirement. • Energy model: different energy mixes, weighted according to the sale volumes, taken into account to represent the main reference markets: <ul style="list-style-type: none"> - Electricity mix, Europe 27 - 2008; - Electricity mix, Tunisia - 2009; - Electricity mix, Egypt - 2009; - Electricity mix, China - 2009.
End of life	The default end of life scenario, as described in the in force PCR, maximizing the impacts.
Software and database used	EIME V5 and its database «CODDE-2018-11»

Product Environmental Profile

UPS
KEOR Compact 10kVA



SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
Global warming	2.85E+04	kgCO₂ eq.	5.43E+02	2%	2.67E+01	< 1%	8.59E-01	< 1%	2.79E+04	98%	5.61E+00	< 1%
Ozone depletion	2.56E-03	kgCFC-11 eq.	6.57E-05	3%	4.57E-08	< 1%	4.33E-09	< 1%	2.49E-03	97%	7.38E-08	< 1%
Acidification of soils and water	7.37E+01	kgSO₂ eq.	1.28E+00	2%	7.56E-01	1%	3.98E-03	< 1%	7.16E+01	97%	2.29E-02	< 1%
Water eutrophication	6.76E+00	kg[PO₄]³⁻ eq.	2.20E-01	3%	7.45E-02	1%	2.49E-03	< 1%	6.43E+00	95%	3.43E-02	< 1%
Photochemical ozone formation	5.83E+00	kgC₂H₄ eq.	1.57E-01	3%	3.75E-02	< 1%	2.83E-04	< 1%	5.63E+00	97%	1.74E-03	< 1%
Depletion of abiotic resources - elements	7.06E-02	kgSb eq.	6.25E-02	89%	9.65E-07	< 1%	3.66E-08	< 1%	8.07E-03	11%	2.80E-07	< 1%
Total use of primary energy	4.33E+05	MJ	1.84E+04	4%	3.41E+02	< 1%	1.19E+01	< 1%	4.14E+05	96%	6.71E+01	< 1%
Net use of fresh water	5.33E+04	m³	2.26E+01	< 1%	2.06E-03	< 1%	1.85E-04	< 1%	5.32E+04	100%	2.67E-03	< 1%
Depletion of abiotic resources - fossil fuels	2.81E+05	MJ	5.29E+03	2%	3.39E+02	< 1%	1.17E+01	< 1%	2.75E+05	98%	6.37E+01	< 1%
Water pollution	1.24E+06	m³	4.84E+04	4%	3.97E+03	< 1%	1.36E+02	< 1%	1.18E+06	96%	7.42E+02	< 1%
Air pollution	1.59E+06	m³	9.96E+04	6%	3.66E+03	< 1%	6.78E+01	< 1%	1.48E+06	93%	4.40E+02	< 1%

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

Registration N°: LGRP-01630-V01.01-EN	Drafting rules: PEP-PCR-ed3-EN-2015 04 02 Supplemented by PSR-0010-ed1.1-2015 10 16
Verifier accreditation N°: VH23	Information and reference documents : www.pep-ecopassport.org
Date of issue: 12-2022	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025:2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
PEP are compliant with XP C08-100-1 : 2016 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804 : 2012 + A1 : 2013	

