

17VATCAPH025

**75 Ω coaxial cable triple shield 17 dB
class A for distribution up to 3 GHz**



DESCRIPTION

Coaxial cable for terrestrial and satellite signal transmission, distribution up to 3 GHz, triple shielding with class A screen efficiency > 85 dB, plastic reels compatible with drum cabinets, available in PVC for indoor installation and PE for outdoor installation.



ADVANTAGES

- Distribution for signals up to 3 GHz
- Class B shielding efficiency >75 dB

Updated: 10/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	17VxTCAPHyy
Core composition	Ø 1.13 +/- 0.01mm
Nominal insulation diameter (mm)	480
Assembly type	Single conductor
Nom. diameter of the outer sheath (mm)	6.80
Braid type	Aluminium
Weight (Kg/Km)	44

ELECTRICAL CHARACTERISTICS

Linear electrical resistance (Ω/Km)	95
-------------------------------------	----

TRANSMISSION CHARACTERISTICS

Propagation speed (%)	88
Characteristic Impedance (Ohms)	75 Ohms

MECHANICAL CHARACTERISTICS

Bending Radius in Mobile Installation	5 x Ø ext
---------------------------------------	-----------

ENVIRONMENTAL CHARACTERISTIC

CPR classification	Eca
Fire behaviour	IEC 60332-1
UV Resistance	NO

ADDITIONAL INFORMATION

Product Packaging	Coil of 25m
-------------------	-------------