1KVXHFA4G4VSHB2

1000V rigid armored LSZH power cables CPR B2ca 1KVXHFA 4G4 grey

DESCRIPTION

The 1KVXHFA armored cables are designed for powering high-power industrial and commercial electrical equipment. Their halogen-free sheath and IEC 60332-3 compliance make them ideal for industrial sites, nuclear facilities, steelworks, chemical plants, and public infrastructure.





ADVANTAGES

- halogen-free (LSZH)
- CPR: B2ca s1a,d1,a1 multicore
- CPR: B2ca s1,d1,a1 single-core
- UV resistance for Northern Europe conditions
- AD7 Possible intermittent, partial, or total freshwater coverage

Updated: 25/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	XHFAPOWER
Construction (mm²)	4 G 4 mm²
Conductor material	Bare copper
Conductor cross-section	4 mm²
Core composition	< 4mm²: solid conductor IEC 60228 class 1 ≥ 6mm²: flexible stranded conductor IEC 60228 class 2
Insulation Material	XLPE
Insulation Identification Method	HD 308 S2
Assembly type	Multi conductors
Inner Sheath Material	LSZH
Overall Armor	Double steel tape
Outer Sheath Material	LSZH
Color	Green
Nom. diameter of the outer sheath (mm)	13.6
Weight (Kg/Km)	420

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	600 / 1000 V
Test voltage (V)	3 kV
Linear electrical resistance (Ω/Km)	conform to IEC 60228 class 1/2

MECHANICAL CHARACTERISTICS

Bending Radius in Fixed Installation	15 x Ø ext
Bending Radius in Mobile Installation	30 x Ø ext
Max Permissible Temperature on Core	90°C
Max Short-Circuit Temperature	250°C
IP rating	AD7

ENVIRONMENTAL CHARACTERISTIC

CPR classification	B2ca s1a, d1, a1
Fire behaviour	IEC 60332-1, IEC 60332-3-24
Fire Behavior Type	Flame retardant IEC 60332-1 Fire retardant IEC 60332-3-24
UV Resistance	Yes
Fixed Use Temperature	-30°C / +70°C

Updated: 25/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

ENVIRONMENTAL CHARACTERISTIC	
Mobile Use Temperature	-5°C / +70°C
Halogen-free Standard	IEC 60754-1/-2 IEC 61034-2
ADDITIONAL INFORMATION	
Product Packaging	Drum of 1000m

Updated: 25/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.