

2100BSHC5

TranXalarm flexible alarm cable 10 x 0.22 mm² LSZH Cca s1,d1,a1 grey



DESCRIPTION

The flexible alarm cables 2x0BSHC, LSZH Cca s1,d1,a1 transmit alarm system signals. TranXalarm cable 10 x 0.22 mm², halogen-free sheath CPR Cca s1,d1,a1 compliant with IEC 60332-3, flexible; discreet installation (white sheath); suitable for industrial, nuclear, and high-rise public buildings (ERP IGH).



ADVANTAGES

- Alarm signal transmission cables
- Discreet installation with white-colored sheath
- LSZH
- CPR Cca s1,d1,a1

AXCITY
/ ADALTRA

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	2xx0BSHCy
Conductor material	Bare copper
Insulation Material	PVC
Assembly type	Multi conductors
Overall Shielding	Alu/pes tape with drain wire
Outer Sheath Material	LSZH
Color	White
Weight (Kg/Km)	38

ELECTRICAL CHARACTERISTICS

Test voltage (V)	1.2 kV
------------------	--------

MECHANICAL CHARACTERISTICS

Bending Radius in Mobile Installation	15 x Ø ext
---------------------------------------	------------

ENVIRONMENTAL CHARACTERISTIC

CPR classification	Cca s1, d1, a1
Fire behaviour	IEC 60332-1, IEC 60332-3
UV Resistance	NO
Fixed Use Temperature	-30°C / +70°C
Mobile Use Temperature	-5°C / +70°C

ADDITIONAL INFORMATION

Product Packaging	Drum of 500m
-------------------	--------------