


90200034SHB2

**HIFLEX-H Cable 2X0.34mm² LIHH
type DIN 47100 color code - 1000m
drum, grey**



DESCRIPTION

HIFLEX-H B2ca cables, type LIHH, transmit analog and digital signals in process and control equipment for measurement, weighing, electronics, and industrial automation. Suitable for fixed or mobile installation, free movement without traction or forced guidance. Recommended for industrial, nuclear, steel, chemical sites, and public infrastructure.



ADVANTAGES

- LSZH
- CPR B2ca s1a,d1,a1

Other structures, sections, color: please contact us.

AXINDUS
/ ADALTRA

Updated: 26/06/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	HIFLEX-H LIHH B2ca
Construction (mm ²)	2 x 0,34 mm ²
Conductor material	Bare copper
Conductor cross-section	0,34 mm ²
Core composition	≤ 0.34mm ² multi-strand ≥ 0.50mm ² IEC60228 class 5
Insulation Material	LSZH Compound
Insulation Identification Method	DIN 47100
Assembly type	Multi conductors
Weight (Kg/Km)	0

ELECTRICAL CHARACTERISTICS

Service Voltage (V)	300 V / 500 V
Test voltage (V)	1.5 kV
Linear electrical resistance (Ω/Km)	Compliant with IEC 60228 class 5 standard

MECHANICAL CHARACTERISTICS

Bending Radius in Mobile Installation	15 x Ø ext
---------------------------------------	------------

ENVIRONMENTAL CHARACTERISTIC

CPR classification	B2ca s1a, d1, a1
Fire behaviour	IEC 60332-1, IEC 60332-3-24
Mobile Use Temperature	-5°C / +70°C

ADDITIONAL INFORMATION

Product Packaging	Drum of 1000m
-------------------	---------------