ACB56PM

6-zone microphone console

DESCRIPTION

The ACB56PM console is compatible with the ACBMAT56120 matrix. It features an adjustable gooseneck and a detachable connector. The light ring indicates status (red = active) and the LED VU meter shows audio levels. Backlit touch keys allow precise use. Zone selectors (1 to 6) and ALL CALL for voice announcements. MP3/AUX button activates playback via USB/ microSD.



ADVANTAGES

- Compatible ACBMAT56120; RJ45 power supply; cascade ≤ 6 units, max 600 m/line
- Zone selection 1–6 and ALL CALL for selective announcements
- MP3/AUX + volume pot.: USB/microSD playback via matrix
- Detachable adjustable gooseneck; active red light ring; VU LED; backlit buttons

Updated: 29/03/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Color	Alu / Black RAL 9005
Maximum distance of amp/mic connection (m)	600

ADDITIONAL INFORMATION

Weight (Kg/U)	0.00

Updated: 29/03/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.