

AU11CD4K22

HDMI audio de-embedder with RCA and TOSLINK output

DESCRIPTION

The AU11CD4K22 extracts audio from an HDMI source while maintaining UHD video transmission up to 4K2K at 60 Hz (YUV 4:4:4). It converts HDMI audio to digital optical (SPDIF) or stereo analog RCA outputs. Compatible with LPCM, Dolby TrueHD, Dolby Digital Plus, Dolby Atmos, and DTS-HD Master Audio formats up to 192 kHz.



ADVANTAGES

- HDMI audio extraction without video loss
- Conversion to optical and analog output
- Supports high-definition audio formats
- UHD compatibility up to 4K 60 Hz
- Optimized audio/video synchronization



Updated: 29/05/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Input(s)	HDMI
Dimensions (L x W x H)	128 x 116.8 x 30
Output(s)	1 x HDMI (for video), 1 x S/PDIF, and 1 x RCA
Supplied with	Alimentation
Power supply	5 V/2.6 A DC
Weight (Kg/U)	0.36

ELECTRICAL CHARACTERISTICS

Power supply	5 V/2.6 A DC
Power Consumption	13

ENVIRONMENTAL CHARACTERISTIC

Relative humidity (%)	20-90
Storage Temperature	-20 to +60 / -4° F to 140° F

ADDITIONAL INFORMATION

Product Packaging	Carton
-------------------	--------