

AUDIOLAN6A26

CAT.6A ETHERNET CABLE - 4 PAIRS - F/UTP - 500 MHz - GREY



DESCRIPTION

Flexible Ethernet cable - Cat.6A - F/UTP - 500 MHz - AWG 26 - Black PVC outer sheath



ADVANTAGES

- High flexibility.
- Low space requirement.
- Available in cords - ON AIR PRO range.



CONSTRUCTION & TECHNICAL PERFORMANCE

Core gauge	AWG26/7
Minimum Insulation Diameter (mm)	0,85
Nominal insulation diameter (mm)	0.90
Maximum Insulation Diameter (mm)	0,95
Assembly type	Pairs
Outer Sheath Material	PVC
Color	Black
Nom. diameter of the outer sheath (mm)	5.90
Shielding type	F/UTP
Weight (Kg/Km)	450

ELECTRICAL CHARACTERISTICS

Mutual Capacity	< 45 pF
-----------------	---------

TRANSMISSION CHARACTERISTICS

Performance Category	Category 6A
Data Transmission Standard	EIA/TIA 568-C.2 Cat6A
Characteristic Impedance (Ohms)	100 Ohms

MECHANICAL CHARACTERISTICS

Bending Radius in Fixed Installation	10 x Ø ext
Bending Radius in Mobile Installation	8 x Ø ext

ENVIRONMENTAL CHARACTERISTIC

CPR classification	Eca
RoHS Compliance	YES
Component Standard	IEC 61156-6 Cat6A

ADDITIONAL INFORMATION

Product Packaging	Drum of 1000m
-------------------	---------------