

CA455L2SAT

TER UHF multiband amplifier 45 dB SAT 45 dB

DESCRIPTION

Wideband amplifier with 5 inputs: FM, Band III-DAB, UHF 1 (470-694 MHz), UHF 2 (470-694 MHz), and SAT. High gains: 30 dB (FM), 35 dB (Band III-DAB), 44 dB (UHF), and 40 dB (SAT). Output level 122 dB μ V (DIN 45004B). Switchable 12/24 Vdc power on UHF, 13 Vdc LNB on SAT. High-rejection 5G filter for mobile interference protection. Class A.



ADVANTAGES

- Wideband amplification with 5 inputs for FM, BIII-DAB, UHF, and SAT
- High gains up to 44 dB in UHF and 40 dB in SAT, output level 122 dB μ V
- Switchable 12/24 Vdc power supply on UHF and 13 Vdc LNB on SAT for flexible installation
- High rejection 5G filter for protection against mobile interference

Updated: 10/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Weight (Kg/U)	2.00
---------------	------