

CCP11

Compression F connector for 11mm cable.

DESCRIPTION

Compression F connector for 11 mm cable, compatible with CCR11CU, CCR11CUD, and CCCR11, featuring quick connection via pressure mechanism, suitable for LTE, 90 dB shielding, and Class A.



ADVANTAGES

- Compatible with CCCR11 cable
- Quick connection via pressure mechanism
- Suitable for LTE, 90 dB shielding
- Class A



Updated: 3/07/2026

This document is confidential and is the property of ADALTRA. ADALTRA holds the copyright, and the document must not be copied or modified in any form, in whole or in part, without the prior written permission of ADALTRA. The specifications contained in this document are non-contractual and may be subject to change without prior notice.

CONSTRUCTION & TECHNICAL PERFORMANCE

Product Type	F Male
Impedance (Ohms)	75
Shielding	90
Cable Diameter (mm)	11
Frequency Band (MHZ)	5-2400
Impedance (Ohms)	75
Weight (Kg/U)	0.25

TRANSMISSION CHARACTERISTICS

Frequency Band (MHZ)	5-2400
----------------------	--------

MECHANICAL CHARACTERISTICS

Product mounting type	Compression
-----------------------	-------------

ADDITIONAL INFORMATION

Product Packaging	Bag
Frequency Band (MHZ)	5-2400